



2097

MILA

Specification according to EN 1307

Type of manufacture	ISO 2424	Tufted 1/10" Cut pile
Pile Fibre composition	ISO 2424	Solution dyed BCF Polyamide 6
Dimensions	EN 994	50 x 50 cm / 19.68" x 19.68" (20 tiles per box)
Primary backing	ISO 2424	Polyester - polyamide fleece
Secondary backing	ISO 2424	Modified bitumen or EcoBase® (Polyver® · Polyscan®)
Total thickness	ISO 1765	7.5 mm 0.30 inch
Effective pile thickness	ISO 1766	3.7 mm 0.15 inch
Total mass	ISO 8543	4250 g/m ² 125.4 oz/yd ²
Total pile mass	ISO 2424	850 g/m ² 25.1 oz/yd ²
Effective pile mass	ISO 8543	545 g/m ² 16.1 oz/yd ²
Pile density	ISO 8543	0.150 g/cm ³ 0.0054 lb/in ³
Number of tufts	ISO 1763	1660 /dm ² 138793 /yd ²
Stroll test	ISO 6356	≤ 2.0 kV
Vertical resistance	ISO 10965	≤ 1x10 ⁹ Ohm
Classification for use	EN 1307	33 Commercial - heavy use
Dimensional stability	EN 986	≤ 0,2%
Flammability	EN 13501-1	B ₁ - s1
Light Reflectance Value (LRV)	BS 8493	See right page per colour
Colour depth (L)	CIELAB	See right page per colour

With bitumen backing



Cradle to Cradle Certified® is a certification mark of NBOC

With EcoBase® backing



Cradle to Cradle Certified® is a certification mark of NBOC



EN 14041
0493-CPD-0002

Manufactured by:

Desso BV
PO Box 169
NL - 5140 AD Waalwijk



* Bitumen only



Mila comprises broadloom carpet and carpet tiles with both common and complementary colours in a densely tufted velour pile. This makes Mila ideal for all areas of a building from corridors to stairs, reception to boardroom. The depth and variety of colour encourages character such as timeless hues for classic elegance and bright accents for contemporary zones.

