

"MRT"

MRT:


The mean radiant temperature is the total radiation located in one point of a room, it's calculated applying the following formula:

$$MRT = \sum_i (t_i F_{v,i})$$



Where:

- t_i : are the indoor surface temperatures of the elements enclosing the space.
- $F_{v,i}$: are the shape factors of the different surfaces from a specific point of the room, and energy leaving the surface a by radiation and reaching the "surface" in P.


Location of the room:



Decomposition of the room:



Shape 1: Internal Wall.



For the shape A:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp [-(a/c) / \tau]\} \{1 - \exp [-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:

SURFACES	(m)
a	0.50
b	2.40
c	1

Then we using the formula we obtain the Fp,l for the surface A in this wall:

Fp,i	0.03032
------	---------

For the shape B:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:

SURFACES	(m)
a	2.65
b	2.40
c	1

Then we using the formula we obtain the Fp,i for the surface A in this wall:

F _{p,i}	0.08266
------------------	---------

For the shape C:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:

SURFACES	(m)
a	0.50
b	0.60
c	1

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0.01541
-----------	---------

For the shape D:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:


SURFACES	(m)
a	2.65
b	0.60
c	1

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0.03994
-----------	---------

SHAPES	$F_{p,i}$
A	0.03032
B	0.08266
C	0.01541
D	0.03994
$\Sigma =$	0.16833

Shape 2: internal wall.



For the shape A:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp [-(a/c) / \tau]\} \{1 - \exp [-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:

SURFACES	(m)
a	2.45
b	2.40
c	0.50

Then we using the formula we obtain the Fp,l for the surface A in this wall:

F _{p,i}	0.10638
------------------	---------

For the shape B:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:

SURFACES	(m)
a	1
b	2.40
c	0.50

Then we using the formula we obtain the Fp,i for the surface A in this wall:

F _{p,i}	0.08444
------------------	---------

For the shape C:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:

SURFACES	(m)
a	2.45
b	0.60
c	0.50

Then we using the formula we obtain the Fp,i for the surface A in this wall:

F _{p,i}	0.06704
------------------	---------

For the shape D:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:



SURFACES	(m)
a	1
b	0.6
c	0.50

Then we using the formula we obtain the Fp,i for the surface A in this wall:

F _{p,i}	0.05658
------------------	---------

SHAPES	F _{p,i}
A	0.10638
B	0.08444
C	0.06704
D	0.05658
Σ=	0.31444

Shape 3: Interior Wall.



For the shape A:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp [-(a/c) / \tau]\} \{1 - \exp [-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:

SURFACES	(m)
a	1
b	2.40
c	2.65

Then we using the formula we obtain the Fp,i for the surface A in this wall:

F _{p,i}	0.01589
------------------	---------

For the shape B:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:

SURFACES	(m)
a	2.45
b	2.40
c	2.65

Then we using the formula we obtain the Fp,i for the surface A in this wall:

F _{p,i}	0.03183
------------------	---------

For the shape C:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:

SURFACES	(m)
a	1
b	0.60
c	2.65

Then we using the formula we obtain the Fp,i for the surface A in this wall:

F _{p,i}	0.00560
------------------	---------

For the shape D:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:


SURFACES	(m)
a	2.45
b	0.60
c	2.65

Then we using the formula we obtain the Fp,i for the surface A in this wall:

F _{p,i}	0.01112
------------------	---------

SHAPES	F _{p,i}
A	0.01589
B	0.03183
C	0.00560
D	0.01112
Σ=	0.06444

Shape 4: Floor.



For the shape A:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp [-(a/c) / \tau]\} \{1 - \exp [-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,116	1,59512	0,12788	1,22643	0,04621	0,04434

And the surfaces are:

SURFACES	(m)
a	0.50
b	1
c	0.60

Then we using the formula we obtain the Fp,i for the surface A in this wall:

F _{p,i}	0.04555
------------------	---------

For the shape B:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,116	1,59512	0,12788	1,22643	0,04621	0,04434

And the surfaces are:

SURFACES	(m)
a	2.65
b	1
c	0.60

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0.08259
-----------	---------

For the shape C:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,116	1,59512	0,12788	1,22643	0,04621	0,04434

And the surfaces are:

SURFACES	(m)
a	0.50
b	2.45
c	0.60

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0.05276
-----------	---------

For the shape D:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,116	1,59512	0,12788	1,22643	0,04621	0,04434

And the surfaces are:


SURFACES	(m)
a	2.65
b	2.45
c	0.60

Then we using the formula we obtain the Fp,i for the surface A in this wall:

F_{p,i}	0.10096
------------------------	----------------

SHAPES	F _{p,i}
A	0.04555
B	0.08259
C	0.05276
D	0.10096
Σ=	0.28186

Shape 5: External Wall.



For the shape A:

The temperature in this shape is 12,72 °C , because it's an external wall.

T (°C)
12,72

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:

SURFACES	(m)
a	2.65
b	2.40
c	2.45

Then we using the formula we obtain the Fp,i for the surface A in this wall:

Fp,i	0.03689
------	---------

For the shape B:

The temperature in this shape is 12,72 °C , because it's an external wall.

T (°C)
12,72

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:

SURFACES	(m)
a	0.50
b	2.40
c	2.45

Then we using the formula we obtain the Fp,i for the surface A in this wall:

F _{p,i}	0.00961
------------------	---------

For the shape C:

The temperature in this shape is 12,72 °C , because it's an external wall.

T (°C)
12,72

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:

SURFACES	(m)
a	2.65
b	0.60
c	2.45

Then we using the formula we obtain the Fp,i for the surface A in this wall:

F _{p,i}	0.03858
------------------	---------

For the shape D:

The temperature in this shape is 12,72 °C , because it's an external wall.

T (°C)
12,72

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:



SURFACES	(m)
a	0.50
b	0.60
c	2.45

Then we using the formula we obtain the Fp,i for the surface A in this wall:

F _{p,i}	0.00348
------------------	---------

SHAPES	F _{p,i}
B	0.03689
A	0.00961
D	0.03858
C	0.00348
Σ=	0.08856

Shape 6: Ceiling.



For the shape A:

The temperature in this shape is 19,26 °C , because it's an external wall.

T (°C)
19,26

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp [-(a/c) / \tau]\} \{1 - \exp [-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,116	1,59512	0,12788	1,22643	0,04621	0,04434

And the surfaces are:

SURFACES	(m)
a	2.65
b	2.45
c	2.40

Then we using the formula we obtain the Fp,i for the surface A in this wall:

F _{p,i}	0.04457
------------------	---------

For the shape B:

The temperature in this shape is 19,26 °C , because it's an external wall.

T (°C)
19,26

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,116	1,59512	0,12788	1,22643	0,04621	0,04434

And the surfaces are:

SURFACES	(m)
a	0.50
b	2.45
c	2.40

Then we using the formula we obtain the Fp,i for the surface A in this wall:

F_{p,i}	0.01291
------------------------	----------------

For the shape C:

The temperature in this shape is 19,26 °C , because it's an external wall.

T (°C)
19,26

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,116	1,59512	0,12788	1,22643	0,04621	0,04434

And the surfaces are:

SURFACES	(m)
a	1
b	2.65
c	2.40

Then we using the formula we obtain the Fp,i for the surface A in this wall:

F_{p,i}	0.02394
------------------------	----------------

For the shape D:

The temperature in this shape is 19,26 °C , because it's an external wall.

T (°C)
19,26

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,116	1,59512	0,12788	1,22643	0,04621	0,04434

And the surfaces are:

SURFACES	(m)
a	0.50
b	1
c	2.40

Then we using the formula we obtain the Fp,i for the surface A in this wall:

F _{p,i}	0.00760
------------------	---------

SHAPES	F _{p,i}
A	0.04457
B	0.01291
C	0.02394
D	0.00760
Σ=	0.08902

	TEMPERATURE (°C)	F _{p,i}	MRT _p
WALL 1	20	0.16833	3.3666
WALL 2	20	0.31444	6.2888
WALL 3	20	0.06444	1.2888
FLOOR 4	20	0.28186	5.6372
WALL 5	12,72	0.08856	1.1264832
CEILING 6	19,29	0.08902	1.7171958

$$\Sigma = 19.425079 \text{ } ^\circ\text{C}$$

$$\text{MRT} = 19.4^\circ\text{C} \approx 19 \text{ } ^\circ\text{C}$$

OPERATING TEMPERATURE:

Once MRT is known, it is possible to calculate the “operating temperature”, that is a good indicator of thermal comfort.

$$\text{Top} = (\text{DBT} + \text{MRT}) / 2$$

Where DBT is the Dry Bulb Temperature and it's 20°C

$$\text{Top} = (20 + 19) / 2 = 19.5 \text{ } ^\circ\text{C}$$

$$\text{Top} = 19.5 \text{ } ^\circ\text{C} \quad 19 \text{ } ^\circ\text{C} < \text{Top} < 20 \text{ } ^\circ\text{C}$$