

"MRT"

FRANCISCO JAVIER MARZO FERRER

MRT:


The mean radiant temperature is the total radiation located in one point of a room, it's calculated applying the following formula:

$$\text{MRT} = \sum_i (t_i F_{v,i})$$



Where:

- t_i : are the indoor surface temperatures of the elements enclosing the space.
- $F_{v,i}$: are the shape factors of the different surfaces from a specific point of the room, and energy leaving the surface a by radiation and reaching the "surface" in P.


Location of the room:



Decomposition of the room:



Shape 1: Interior Wall.



For the shape A:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:

SURFACES	(m)
a	1,98
b	2
c	1,58

Then we using the formula we obtain the Fp,i for the surface A in this wall:

Fp,i	0,05558
------	---------

For the shape B:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:

SURFACES	(m)
a	3,07
b	2
c	1,58

Then we using the formula we obtain the Fp,i for the surface A in this wall:

F _{p,i}	0,06708
------------------	---------

For the shape C:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:

SURFACES	(m)
a	1,98
b	1
c	1,58

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,04015
-----------	---------

For the shape D:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:


SURFACES	(m)
a	3,07
b	1
c	1,58

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,04788
-----------	---------

SHAPES	$F_{p,i}$
A	0,05558
B	0,06708
C	0,04015
D	0,04788
$\Sigma =$	0,21069

Shape 2:



For the shape A:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:

SURFACES	(m)
a	2,02
b	2
c	1,98

Then we using the formula we obtain the Fp,i for the surface A in this wall:

$F_{p,i}$	0,04563
-----------	---------

For the shape B:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:

SURFACES	(m)
a	1,58
b	2
c	1,98

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,03934
-----------	---------

For the shape C:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:

SURFACES	(m)
a	2,02
b	1
c	1,98

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,03142
-----------	---------

For the shape D:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:


SURFACES	(m)
a	1,58
b	1
c	1,98

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,02719
-----------	---------

SHAPES	$F_{p,i}$
A	0,04563
B	0,03934
C	0,03142
D	0,02719
$\Sigma =$	0,14358

Shape 3: Wall.



For the shape A:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:

SURFACES	(m)
a	1,58
b	2
c	3,07

Then we using the formula we obtain the Fp,i for the surface A in this wall:

F_{p,i}	0,02343
------------------------	---------

For the shape B:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the F_v, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the F_{p,i} are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:

SURFACES	(m)
a	2,02
b	2
c	3,07

Then we using the formula we obtain the F_{p,i} for the surface A in this wall:

F_{p,i}	0,02793
------------------------	---------

For the shape C:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:

SURFACES	(m)
a	1,58
b	1
c	3,07

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,01485
-----------	---------

For the shape D:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:


SURFACES	(m)
a	2,02
b	1
c	3,07

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,01766
-----------	---------

SHAPES	$F_{p,i}$
A	0,02343
B	0,02793
C	0,01485
D	0,01766
$\Sigma =$	0,08387

Shape 4: FLOOR.



For the shape A:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,116	1,59512	0,12788	1,22643	0,04621	0,04434

And the surfaces are:

SURFACES	(m)
a	1,98
b	1,58
c	1

Then we using the formula we obtain the Fp,i for the surface A in this wall:

F_{p,i}	0,05185
------------------------	----------------

For the shape B:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,116	1,59512	0,12788	1,22643	0,04621	0,04434

And the surfaces are:

SURFACES	(m)
a	3,07
b	1,58
c	1

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,06089
-----------	---------

For the shape C:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp [-(a/c) / \tau]\} \{1 - \exp [-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,116	1,59512	0,12788	1,22643	0,04621	0,04434

And the surfaces are:

SURFACES	(m)
a	1,98
b	2,02
c	1

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,05810
-----------	---------

For the shape D:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,116	1,59512	0,12788	1,22643	0,04621	0,04434

And the surfaces are:


SURFACES	(m)
a	3,07
b	2,02
c	1

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,06846
-----------	---------

SHAPES	$F_{p,i}$
A	0,05185
B	0,06089
C	0,05810
D	0,06846
$\Sigma =$	0,2393

Shape 5: External Wall.



For the shape A:

The temperature in this shape is 12,72 °C , because it's an external wall.

T (°C)
12,72

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:

SURFACES	(m)
a	3,07
b	2
c	2,02

Then we using the formula we obtain the Fp,l for the surface A in this wall:

F_{p,i}	0,05520
------------------------	----------------

For the shape B:

The temperature in this shape is 12,72 °C , because it's an external wall.

T (°C)
12,72

To calculate the F_v, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the F_{p,i} are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:

SURFACES	(m)
a	1,98
b	2
c	2,02

Then we using the formula we obtain the F_{p,i} for the surface A in this wall:

F_{p,i}	0,04422
------------------------	----------------

For the shape C:

The temperature in this shape is 12,72 °C , because it's an external wall.

T (°C)
12,72

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:

SURFACES	(m)
a	3,07
b	1
c	2,02

Then we using the formula we obtain the Fp,i for the surface A in this wall:

F _{p,i}	0,03752
------------------	---------

For the shape D:

The temperature in this shape is 12,72 °C , because it's an external wall.

T (°C)
12,72

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp [-(a/c) / \tau]\} \{1 - \exp [-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,120	1,24186	0,16730	0,61648	0,08165	0,05128

And the surfaces are:


SURFACES	(m)
a	1,98
b	1
c	2,02

Then we using the formula we obtain the Fp,i for the surface A in this wall:

Fp,i	0,03033
------	---------

SHAPES	Fp,i
B	0,04422
A	0,05520
D	0,03033
C	0,03752
$\Sigma =$	0,16727

Shape 6: Ceiling.



For the shape A:

The temperature in this shape is 19,26 °C , because it's an external wall.

T (°C)
19,26

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,116	1,59512	0,12788	1,22643	0,04621	0,04434

And the surfaces are:

SURFACES	(m)
a	1,98
b	2,02
c	2

Then we using the formula we obtain the Fp,i for the surface A in this wall:

F_{p,i}	0,02717
------------------------	----------------

For the shape B:

The temperature in this shape is 19,26 °C , because it's an external wall.

T (°C)
19,26

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp [-(a/c) / \tau]\} \{1 - \exp [-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,116	1,59512	0,12788	1,22643	0,04621	0,04434

And the surfaces are:

SURFACES	(m)
a	3,07
b	2,02
c	2

Then we using the formula we obtain the Fp,i for the surface A in this wall:

F_{p,i}	0,03532
------------------------	----------------

For the shape C:

The temperature in this shape is 19,26 °C , because it's an external wall.

T (°C)
19,26

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,116	1,59512	0,12788	1,22643	0,04621	0,04434

And the surfaces are:

SURFACES	(m)
a	1,98
b	1,58
c	2

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,02301
-----------	---------

For the shape D:

The temperature in this shape is 19,26 °C , because it's an external wall.

T (°C)
19,26

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp [-(a/c) / \tau]\} \{1 - \exp [-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,116	1,59512	0,12788	1,22643	0,04621	0,04434

And the surfaces are:

SURFACES	(m)
a	3,07
b	1,58
c	2

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,02988
-----------	---------

SHAPES	$F_{p,i}$
A	0,02717
B	0,03532
C	0,02301
D	0,02988
$\Sigma =$	0,11538

	TEMPERATURE (°C)	F _{p,i}	MRT _p
WALL 1	20	0,21069	4,2138
WALL 2	20	0,14358	2,8716
WALL 3	20	0,08387	1,6774
FLOOR 4	20	0,2393	4,786
WALL 5	12,72	0,16727	2,1276744
CEILING 6	19,29	0,11538	2,2256802

$$\Sigma = 17,9 \text{ °C}$$

$$\text{MRT} = 17,9 \text{ °C} \approx 18 \text{ °C}$$

OPERATING TEMPERATURE:

Once MRT is known, it is possible to calculate the “operating temperature”, that is a good indicator of thermal comfort.

$$\text{Top} = (\text{DBT} + \text{MRT}) / 2$$

Where DBT is the Dry Bulb Temperature and it's 20°C

$$\text{Top} = (20 + 18) / 2 = 19 \text{ °C}$$

$$\text{Top} = 19 \text{ °C} \quad 19 \text{ °C} < \text{Top} < 20 \text{ °C}$$