

GRAVEL. FOR ROOF PROTECTION, WITH DIFFERENT STONE SIZES TO FILTER THE WATER.  
 $S = 7 \text{ cm. } \lambda = 2 \text{ W/mK}$

UNCOUPLING LAYER. SYNTHETIC NET FIBER TO UNCOUPLING AND PROTECT THE WATERPROOF LAYER.  
 $S = 0,2 \text{ cm. } \lambda = 0,05 \text{ W/mK}$

RIGID FOAM INSULATION OF XPS. (EXTRUDED POLYSTYREN) WHICH HAS A CLOSED CELL STRUCTURE.  
 $S = 12 \text{ cm. } \lambda = 0,035 \text{ W/mK}$

UNCOUPLING LAYER. SYNTHETIC NET FIBER TO UNCOUPLING AND PROTECT THE WATERPROOF LAYER.  
 $S = 0,2 \text{ cm. } \lambda = 0,05 \text{ W/mK}$

WATER PROOF LAYER OF MODIFIED BITUMEN SBS. WITH REINFORCEMENT OF POLIESTER FIBER WITH NONSTICK FINISHING.  
 $S = 0,5 \text{ cm } \lambda = 0,23 \text{ W/mK}$

CONCRETE. USED FOR BUILD UP OF ROOF SLOPE.  $S = 5,7 \text{ cm}$

WAFFLE SLAB OF REINFORCED CONCRETE  $S = 30 \text{ cm. } \lambda = 1,16 \text{ W/mK}$

FALSE CEALING OF PLASTER.  $S = 1,5 \text{ cm.}$

COPING.

SHEET ROOK PANEL- PLADUR -N. PLASTERBOARD.  $S = 1,5 \text{ cm. } \lambda = 0,035 \text{ W/mK}$

VAPOR BARRIER  $S = 0,5 \text{ cm } \lambda = 0,23 \text{ W/mK}$

SOFT INSULATION OF FIBER WOOL  $S = 10 \text{ cm. } \lambda = 0,035 \text{ W/mK}$

REINFORCED CONCRETE.  $S = 40 \text{ cm. } \lambda = 1,16 \text{ W/mK}$


AIR SPRING SP 10 CM  $\lambda = 0,095 \text{ W/mK}$  UPRIGHT ALUMINUM HITCH BOLTS TO THE FRONT

MARBLE PLATE DIM. 25 X 42 X 0.35 WHITE  $\lambda = 3.5 \text{ W/mK}$

**01 WALL SECTIONS DETAIL 5**  
 A-5.20 SCALE: 1/5



COURSE:  
 TECHNOLOGICAL DESIGN



SCHOOL:  
 INSTRUCTORS:  
 G. MASERA  
 O. PAGANI

TUTORS:  
 M. BRASCA  
 M. SAUCHELLI

ISSUE DATES:  
 1. 17-05-2011  
 2. 31-05-2011  
 3. 07-06-2011  
 4. 14-06-2011  
 5. 21-06-2011  
 6.  
 7.  
 8.

SHEET AUTHOR(S):  
 MARZO FERRER, FCO. JAVIER

PROJECT:  
 ENVIRONMENTAL HOME

LECCO, LOMBARDIA  
 ITALIA

SHEET TITLE:  
 WALL SECTIONS DETAIL

SHEET No.:  
 A-5.20

FILE NAME:  
 F.T. & C. .DWG