

"MRT"

BEDROOM

Alejandro García Aguilera

MRT:


The mean radiant temperature is the total radiation located in one point of a room, it's calculated applying the following formula:

$$MRT = \sum_i (t_i F_{v,i})$$





Where:

- t_i : are the indoor surface temperatures of the elements enclosing the space.
- $F_{v,i}$: are the shape factors of the different surfaces from a specific point of the room, and energy leaving the surface a by radiation and reaching the "surface" in P.
-


Location of the room:



Decomposition of the room:



Shape 1: Interior Wall.



For the shape A:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp [-(a/c) / \tau]\} \{1 - \exp [-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is sitting , and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,118	1,2159	0,16890	0,71739	0,08733	0,05267

And the surfaces are:

SURFACES	(m)
a	2,00
b	2,40
c	1,4

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,06047
-----------	---------

For the shape B:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,118	1,2159	0,16890	0,71739	0,08733	0,05267

And the surfaces are:

SURFACES	(m)
a	2,70
b	2,40
c	1,44

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,06859
-----------	---------

For the shape C:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F^*	A	B	C	D	E
0,118	1,2159	0,16890	0,71739	0,08733	0,05267

And the surfaces are:

SURFACES	(m)
a	2,00
b	0,60
c	1,44

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,02880
-----------	---------

For the shape D:

The temperature in this shape is 20 °C , because it's an interior wall.

T (°C)
20

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,118	1,2159	0,16890	0,71739	0,08733	0,05267

And the surfaces are:


SURFACES	(m)
a	2,70
b	0,60
c	1,44

Then we using the formula we obtain the Fp,i for the surface A in this wall:

Fp,i	0,03222
------	---------

SHAPES	Fp,i
A	0,06047
B	0,06859
C	0,02880
D	0,03222
Σ=	0,19008

Shape WALL 2:



For the shape A:

The temperature in this shape is 19,04 °C , because it's an EXTERIOR wall (Stone).

T (°C)
19,04

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp [-(a/c) / \tau]\} \{1 - \exp [-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,118	1,2159	0,16890	0,71739	0,08733	0,05267

And the surfaces are:

SURFACES	(m)
a	1,44
b	2,40
c	2,70

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,02613
-----------	---------

For the shape B:

The temperature in this shape is 19,04 °C , because it's an external wall (stone).

T (°C)
19,04

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,118	1,2159	0,16890	0,71739	0,08733	0,05267

And the surfaces are:

SURFACES	(m)
a	1,44
b	2
c	2,70

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,02613
-----------	---------

For the shape C:

The temperature in this shape is 19,04 °C , because it's an external wall (stone).

T (°C)
19,04

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp [-(a/c) / \tau]\} \{1 - \exp [-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,118	1,2159	0,16890	0,71739	0,08733	0,05267

And the surfaces are:

SURFACES	(m)
a	1,44
b	0,60
c	2,70

Then we using the formula we obtain the Fp,i for the surface A in this wall:

Fp,i	0,00998
------	---------

For the shape D:

The temperature in this shape is 19,04 °C , because it's an external wall (stone).

T (°C)
19,04

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp [-(a/c) / \tau]\} \{1 - \exp [-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F^*	A	B	C	D	E
0,118	1,2159	0,16890	0,71739	0,08733	0,05267

And the surfaces are:


SURFACES	(m)
a	1,44
b	0,60
c	2,70

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,00998
-----------	---------

SHAPES	$F_{p,i}$
A	0,02613
B	0,02613
C	0,00998
D	0,00998
$\Sigma =$	0,07222

Shape 3: Exterior Wall.



For the shape A:

The temperature in this shape is 19,04 °C , because it's an external wall (stone).

T (°C)
19,04

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,118	1,2159	0,16890	0,71739	0,08733	0,05267

And the surfaces are:

SURFACES	(m)
a	2,70
b	2,40
c	1,44

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,06859
-----------	---------

For the shape B:

The temperature in this shape is 19,04 °C , because it's an external wall (stone).

T (°C)
19,04

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F^*	A	B	C	D	E
0,118	1,2159	0,16890	0,71739	0,08733	0,05267

And the surfaces are:

SURFACES	(m)
a	2,00
b	2,40
c	1,44

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,06047
-----------	---------

For the shape C:

The temperature in this shape is 19,04°C , because it's an external wall (stone).

T (°C)
19,04

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,118	1,2159	0,16890	0,71739	0,08733	0,05267

And the surfaces are:

SURFACES	(m)
a	2,70
b	0,60
C	1,44

Then we using the formula we obtain the Fp,i for the surface A in this wall:

F _{p,i}	0,0322
------------------	--------

For the shape D:

The temperature in this shape is 19,04°C , because it's an external wall (stone).

T (°C)
19,04

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,118	1,2159	0,16890	0,71739	0,08733	0,05267

And the surfaces are:


SURFACES	(m)
a	2,70
b	0,60
c	1,44

Then we using the formula we obtain the Fp,i for the surface A in this wall:

Fp,i	0,02880
------	---------

SHAPES	Fp,i
A	0,06859
B	0,06047
C	0,0322
D	0,02880
Σ=	0,19006

Shape: FLOOR.



For the shape A:

The temperature in this shape is 19,10°C.

T (°C)
19,10

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,116	1,39569	0,01302	0,95093	0,07967	0,05458

And the surfaces are:

SURFACES	(m)
a	1,44
b	2,70
c	0,60

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,09027
-----------	---------

For the shape B:

The temperature in this shape is 19,10 °C .

T (°C)
19,10

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,116	1,39569	0,01302	0,95093	0,07967	0,05458

And the surfaces are:

SURFACES	(m)
a	1,44
b	2,70
c	0,60

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,09027
-----------	---------

For the shape C:

The temperature in this shape is 19,10°C.

T (°C)
19,10

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,116	1,39569	0,01302	0,95093	0,07967	0,05458

And the surfaces are:

SURFACES	(m)
a	1,44
b	2,00
c	0,60

Then we using the formula we obtain the Fp,i for the surface A in this wall:

F_{p,i}	0,08647
------------------------	----------------

For the shape D:

The temperature in this shape is 19,10°C.

T (°C)
19,10

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,116	1,39569	0,01302	0,95093	0,07967	0,05458

And the surfaces are:


SURFACES	(m)
a	1,44
b	2,00
c	0,60

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,08647
-----------	---------

SHAPES	$F_{p,i}$
A	0,09027
B	0,09027
C	0,08647
D	0,08647
$\Sigma =$	0,35348

Shape 4: External Wall.



For the shape A:

The temperature in this shape is 12,72 °C , because it's an external wall.

T (°C)
12,72

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,118	1,2159	0,16890	0,71739	0,08733	0,05267

And the surfaces are:

SURFACES	(m)
a	1,44
b	2,40
c	2,00

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,03696
-----------	---------

For the shape B:

The temperature in this shape is 12,72 °C , because it's an external wall.

T (°C)
12,72

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,118	1,2159	0,16890	0,71739	0,08733	0,05267

And the surfaces are:

SURFACES	(m)
a	1,44
b	2,40
c	2,00

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,03696
-----------	---------

For the shape C:

The temperature in this shape is 12,72 °C , because it's an external wall.

T (°C)
12,72

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp [-(a/c) / \tau]\} \{1 - \exp [-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,118	1,2159	0,16890	0,71739	0,08733	0,05267

And the surfaces are:

SURFACES	(m)
a	1,44
b	0,60
c	2,00

Then we using the formula we obtain the Fp,i for the surface A in this wall:

Fp,i	0,01566
------	---------

For the shape D:

The temperature in this shape is 12,72 °C , because it's an external wall.

T (°C)
12,72

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp [-(a/c) / \tau]\} \{1 - \exp [-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F^*	A	B	C	D	E
0,118	1,2159	0,16890	0,71739	0,08733	0,05267

And the surfaces are:


SURFACES	(m)
a	1,44
b	0,60
c	2,00

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,01566
-----------	---------

SHAPES	$F_{p,i}$
B	0,03696
A	0,03696
D	0,01566
C	0,01566
$\Sigma =$	0,10524

Shape: Ceiling.



For the shape A:

The temperature in this shape is 19,49 °C.

T (°C)
19,49

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,116	1,39569	0,01302	0,95093	0,07967	0,05458

And the surfaces are:

SURFACES	(m)
a	1,44
b	2,70
c	2,40

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,02621
-----------	---------

For the shape B:

The temperature in this shape is 19,49 °C.

T (°C)
19,49

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,116	1,39569	0,01302	0,95093	0,07967	0,05458

And the surfaces are:

SURFACES	(m)
a	1,44
b	2,70
c	2,40

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,02621
-----------	---------

For the shape C:

The temperature in this shape is 19,49 °C.

T (°C)
19,49

To calculate the F_v , it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the $F_{p,i}$ are:

F*	A	B	C	D	E
0,116	1,39569	0,01302	0,95093	0,07967	0,05458

And the surfaces are:

SURFACES	(m)
a	1,44
b	2,00
c	2,40

Then we using the formula we obtain the $F_{p,i}$ for the surface A in this wall:

$F_{p,i}$	0,02210
-----------	---------

For the shape D:

The temperature in this shape is 19,49 °C.

T (°C)
19,49

To calculate the Fv, it's necessary apply this formula:

$$F_{p,i} = F^* \{1 - \exp[-(a/c) / \tau]\} \{1 - \exp[-(b/c) / \gamma]\}$$

$$\tau = A + B a/c$$

$$\gamma = C + D b/c + E a/c$$

How the Observer is stand up, and we need to calculate a wall, the values that we need use to calculate the Fp,i are:

F*	A	B	C	D	E
0,116	1,39569	0,01302	0,95093	0,07967	0,05458

And the surfaces are:

SURFACES	(m)
a	1,44
b	2,00
c	2,40

Then we using the formula we obtain the Fp,i for the surface A in this wall:

Fp,i	0,002210
------	----------

SHAPES	Fp,i
A	0,02621
B	0,02621
C	0,002210
D	0,002210
Σ=	0,09662

	TEMPERATURE (°C)	F _{p,i}	MRT _p
WALL 1	20	0,19008	3,80
WALL 2	19,40	0,07222	1,375
WALL 3	19,04	0,19006	3,618
WALL 4	12,72	0,10524	1,3386
FLOOR	19,10	0,35348	6,7514
CEILING	19,49	0,09662	1,8831

$$\Sigma = 18,76^{\circ}\text{C}$$

$$\text{MRT} = 18,76^{\circ}\text{C}$$

OPERATING TEMPERATURE:

Once MRT is known, it is possible to calculate the “operating temperature”, that is a good indicator of thermal comfort.

$$\text{Top} = (\text{DBT} + \text{MRT}) / 2$$

Where DBT is the Dry Bulb Temperature and it's 20°C

$$\text{Top} = (20 + 18,76) / 2 = 19,38^{\circ}\text{C}$$

$$\text{Top} = 19,38^{\circ}\text{C} \quad 19^{\circ}\text{C} < \text{Top} < 20^{\circ}\text{C}$$