

Table of contents

| | |
|---|-----------|
| Acronyms | v |
| Notation | ix |
| 1 Introduction | 1 |
| 1.1 Background | 2 |
| 1.1.1 Towards Fifth Generation (5G) | 2 |
| 1.1.2 5G Requirements | 3 |
| 1.1.3 Use Cases | 4 |
| 1.1.4 5G Enablers | 6 |
| 1.1.5 5G Spectrum Requirements | 8 |
| 1.1.6 5G Channel Model Requirements and Propagation Scenarios | 10 |
| 1.2 State of the Art Analysis | 11 |
| 1.2.1 5G Radio Propagation Channel | 11 |
| 1.2.2 Propagation Channel models above 6 GHz | 15 |
| 1.2.3 Serious Game Engineering | 18 |
| 1.3 Problem and Thesis scope | 21 |
| 1.4 Thesis objectives | 22 |
| 1.5 Thesis outline | 23 |
| 1.6 Thesis publications | 23 |
| 2 Evaluation of Path Loss Channel models for 5G | 25 |
| 2.1 Introduction | 26 |
| 2.2 IMT-2020 and 3GPP Large-Scale Channel Model | 26 |
| 2.2.1 Large-Scale Model | 27 |
| 2.2.2 Small-Scale Model | 27 |
| 2.2.3 Loss Probability | 28 |
| 2.3 NYU Propagation Channel Model | 28 |

TABLE OF CONTENTS

| | | |
|----------|---|-----------|
| 2.3.1 | Large-Scale Model | 29 |
| 2.3.2 | Small-Scale Model | 29 |
| 2.3.3 | Loss Probability | 29 |
| 2.4 | METIS Map-Based Channel Model | 30 |
| 2.4.1 | Large-Scale Model | 30 |
| 2.4.2 | Small-Scale Model | 32 |
| 2.5 | Evaluation of Large-Scale Path Loss Channel Models below 6 GHz | 33 |
| 2.6 | Evaluation of Large Scale Path Loss Channel Models above 6 GHz | 36 |
| 2.7 | Conclusions | 41 |
| 3 | Unity3D Game Engine | 43 |
| 3.1 | Unity Game Engine Description | 43 |
| 3.2 | Unity Interface | 44 |
| 3.3 | Geometry in Unity | 45 |
| 3.3.1 | GameObjects | 45 |
| 3.3.2 | Meshes | 45 |
| 3.4 | Lighting Techniques | 46 |
| 3.4.1 | Real-time Lighting | 46 |
| 3.4.2 | Baked Lighting | 46 |
| 3.4.3 | Pre-Calculated Lighting | 47 |
| 3.5 | Light Types | 47 |
| 3.6 | Light Physics Engine: Ray Tracing | 50 |
| 3.6.1 | Global Illumination | 50 |
| 3.6.2 | Reflections | 52 |
| 3.6.3 | Shadows | 54 |
| 3.7 | Object Properties | 54 |
| 3.7.1 | Materials and Shaders | 54 |
| 3.7.2 | Textures | 55 |
| 3.8 | User Interface | 55 |
| 4 | Light Intensity Model for 5G | 57 |
| 4.1 | Introduction | 58 |
| 4.2 | Light Intensity Model | 58 |
| 4.2.1 | Concept Details | 59 |
| 4.3 | Development of the Scenario of New York University in Unity . | 60 |
| 4.4 | Acquisition of Light Intensity Values | 61 |
| 4.5 | Measurement Campaign of Propagation Losses at 28 and 73 GHz at NYU | 62 |
| 4.6 | Light Intensity Model Calibration | 63 |
| 4.7 | Model Accuracy | 66 |
| 4.8 | Computational Complexity | 69 |

TABLE OF CONTENTS

| | | |
|-------------------|---|------------|
| 4.9 | Conclusions | 70 |
| 5 | Extension of LIM | 71 |
| 5.1 | Introduction | 71 |
| 5.2 | Diffuse Scattering Measurement Campaign at 26 to 40 GHz | 73 |
| 5.3 | Ray Tracing Calibration | 76 |
| 5.3.1 | Analytical Results | 81 |
| 5.4 | LIM Extension | 94 |
| 5.4.1 | Light Rendering Process | 96 |
| 5.4.2 | Results | 97 |
| 5.4.3 | Computational complexity | 103 |
| 5.5 | Conclusions | 103 |
| 6 | A Multi-Purpose Visualization Platform for 5G based on Unity | 105 |
| 6.1 | Platform description | 105 |
| 6.2 | Simulator Layout | 107 |
| 6.2.1 | Block I: External Inputs | 107 |
| 6.2.2 | Block II: Logical Layer | 109 |
| 6.2.3 | Block III: Use Case Implementation | 109 |
| 6.2.4 | Block IV: Simulation | 111 |
| 6.2.5 | Block V: Presentation Layer | 111 |
| 6.3 | Use Cases | 112 |
| 6.3.1 | Light Intensity Model (LIM) 5G | 112 |
| 6.3.2 | Vehicular Communications Simulation Tool | 115 |
| 6.3.3 | Ray Tracing Simulator for Millimeter Wave (mmW) | 117 |
| 6.4 | Conclusions | 118 |
| 7 | Conclusions and future work | 121 |
| 7.1 | Concluding remarks | 121 |
| 7.2 | Future research lines | 124 |
| Appendices | | 127 |
| A | Unity3D Ray Tracing Implementation | 127 |
| References | | 133 |