

Contents

Acknowledgments i

Abstract iv

Resum vi

Resumen ix

Contents xii

List of figures xviii

List of tables xxi

Nomenclature xxiii

Chapter 1 Introduction 28

1.1 Motivation 28

1.2 Background and research context 34

1.2.1 Maximum performance of a heating process 34

1.2.2 Characteristics of the heat sink (DHW production) 38

1.2.3 Characteristics of the heat source (wastewater heat recovery) 39

1.2.4 Main challenges of DHW production based on heat pumps with wastewater heat recovery 40

1.2.5 Identified gaps and research goals 48

1.3 Objectives 50

1.4 Structure 53

Chapter 2 Exergy analysis on a heat pump working between a heat sink and a heat source of finite heat capacity rate 59

2.1 Abstract 59

2.2 Nomenclature 60

2.3 Introduction 61

2.4 Methodology 65

2.4.1 Theoretical basis 65

2.4.2 Case study 68

2.5 Results and discussion 72

2.5.1 Exergy analysis as a function of temperature lift in the condenser 73

2.5.2 Exergy analysis as a function of temperature lift in the evaporator 80

2.5.3 Exergy analysis of the whole system as a function of subcooling and superheat 85

2.5.4 Optimal operation for different applications 87

2.6 Conclusions 88

2.7 Acknowledgements 89

2.8 References 90

Chapter 3 Study of different subcooling control strategies in order to enhance the performance of a heat pump 95

3.1 Abstract 95

3.2 Nomenclature 96

3.3 Introduction 97

3.4 Methodology 100

3.4.1 Studied system 100

3.4.2 Theoretical analysis 102

3.5 Results 105

3.5.1 Optimal subcooling control based on a linear approach 105

3.5.2 Optimal subcooling control based on the temperature approach 108

3.6 Conclusions 121

3.7 Acknowledgements 122

3.8 References 123

Chapter 4 Optimized water to water heat pump design for low-temperature waste heat recovery based on subcooling control 128

4.1 Abstract 128

4.2 Nomenclature 129

4.3 Introduction 130

4.4 Heat Pump design 133

4.5 Experimental setup and test procedure 135

4.5.1 Test rig	135
4.5.2 Sensors and error analysis	136
4.5.3 Experimental campaign	137
4.6 Results	140
4.6.1 Reference conditions	140
4.6.2 Water heating limit conditions	144
4.6.3 Evaporator conditions	146
4.7 Conclusions	148
4.8 Acknowledgements	149
4.9 References	149
Chapter 5 Optimal sizing of a heat pump booster for sanitary hot water production to maximize benefit for the substitution of gas boilers	155
5.1 Abstract	155
5.2 Nomenclature	156
5.3 Introduction	158
5.4 Description of the model	160
5.4.1 Description of the system	160
5.4.2 Model equations	162
5.3.2.1. Thermodynamic problem	162
5.3.2.2. Economic problem	166
5.3.2.1. System maximization equation	168
5.5 Performed analysis	169
5.6 Results and discussion	172
5.6.1 Study of a heat pump vs system heat exchanger-heat pump	172
5.6.2 Study of the optimal size of HPR to maximize the Benefit.	175
5.7 Conclusions	185
5.8 Acknowledgements	186
5.9 References	186
Chapter 6	189
6.1 Abstract	189

6.2 Nomenclature	190
6.3 Introduction	191
6.3.1 Motivation	191
6.4 Developed Model	194
6.4.1 Heat source and heat sink characterization	194
6.4.2 Model of the SHP	196
6.4.3 Model description	201
6.5 Performed studies	204
6.6 Results	208
6.7 Conclusions	220
6.8 Acknowledgements	221
6.9 References	222
Chapter 7	227
7.1 Abstract	227
7.2 Nomenclature	228
7.3 Introduction	229
7.4 Methodology	233
7.4.1 Heat sink characterization	233
7.4.2 Heat source characterization	234
7.4.3 Description of the system	238
7.5 Methodology	242
7.6 Performed study	249
CASE 1: Infinite availability of grey water	250
CASE 2: Finite availability of grey water and constant time	251
CASE 3: Finite and not constant availability of grey water	252
7.7 Results	254
7.8 Conclusions	261
7.9 Acknowledgements	262
7.10 References	263
Chapter 8 Discussion of the main results, general conclusions and future work	271

8.1 Discussion of the main results	271
8.2 General conclusions	280
8.2.1 From the HP design point of view	280
8.2.2 From the system point of view	280
8.3 Future work	282
8.3.1 Heat pump design	282
8.3.2 System integration	282
8.4 Publications	283
8.4.1 In peer-reviewed journals	283
8.4.2 In conference proceedings	283
References	286
Appendix A	294
Experimental setup and test conditions	294
A.1 Heat pump designs	294
A.2 Experimental setup	295
A.2.1 Propane cycle (Prototype configurations)	298
A.2.2 Water loop for the heat source (Evaporator)	299
A.2.3 Water loop for the heat sink (Condenser)	300
A.2.4 Water/glycol and chiller working with R410A loops	302
A.3 Sensors and error analysis	303
A.4 Performed tests	304
Appendix B Refrigerant distribution in the evaporator	309
B.1 Experimental and theoretic heat pump performance	309
B.2 Distribution of the refrigerant in the evaporator	311
Appendix C	315
C.1 Auxiliary consumption	315
C.2 Uncertainty	317
C.3 Experimental results for the 0K1V design	318
C.4 Results for the 10K2Vdesign	331