

# Contents

Preface . . . . .	iii
Aim of thesis . . . . .	iv
Thesis outline and publication history . . . . .	iv
Acknowledgements . . . . .	viii
Financial support . . . . .	ix
Contents . . . . .	xvii
List of Figures . . . . .	xxiii
List of Tables . . . . .	xxxii
List of Acronyms . . . . .	xxxiii
1 Introduction . . . . .	1
1.1 Sampling methods . . . . .	1
1.2 Networked control systems. . . . .	3
1.2.1 Advantages . . . . .	4
1.2.2 Disadvantages . . . . .	5
1.2.3 Types of networked control systems . . . . .	7
1.3 Event-triggered control . . . . .	10
1.3.1 Time Triggered Control (TTC) and Event Triggered Control (ETC) . . . . .	10
1.3.2 Periodic Event-Triggered Control. . . . .	11
1.4 Packet-based control. . . . .	14

1.5 Aspects on frequency response . . . . .	16
1.6 Literature review . . . . .	16
1.6.1 Papers on event-triggered control . . . . .	16
1.6.2 Papers on packet-based control . . . . .	17
1.6.3 Papers on multi-rate frequency analysis. . . . .	17
1.6.4 Papers on prediction-based techniques . . . . .	18
1.6.5 Papers on multi-rate control. . . . .	18
References . . . . .	21
2 Paper 1. Control of the rotary inverted pendulum through threshold-based communication . . . . .	29
2.1 Introduction . . . . .	29
2.2 Conventional control of the rotary inverted pendulum . . . . .	33
2.3 Threshold-based control of the rotary inverted pendulum . . . . .	38
2.3.1 Optimal threshold values determination . . . . .	41
2.3.2 Experimental results with threshold-based control . . . . .	46
2.4 Conclusions and future work . . . . .	48
References . . . . .	51
3 Paper 2. A packet-based dual-rate PID control strategy for a slow-rate sensing networked control system . . . . .	55
3.1 Introduction . . . . .	56
3.2 Problem description . . . . .	58
3.3 Packet-based control strategy. Prediction stage. . . . .	63
3.3.1 Slow-rate PI controller . . . . .	65
3.3.2 Rate converter . . . . .	66
3.3.3 Fast-rate PD controller . . . . .	67
3.3.4 Prediction Stage . . . . .	68
3.4 Stability analysis . . . . .	71
3.4.1 Closed-loop model via lifting . . . . .	71
3.4.2 Closed-loop stability . . . . .	73
3.5 Simulation results . . . . .	74
3.5.1 Simulation data . . . . .	74

3.5.2 Data analysis via cost indexes. . . . .	77
3.6 Experimental results. . . . .	79
3.7 Conclusions. . . . .	81
References . . . . .	83
4 Paper 3. Dual-rate sampled-data systems. Some interesting con- sequences from its frequency response analysis	87
4.1 Motivation . . . . .	88
4.2 DRS frequency response computation: a classical interpretation. . . . .	89
4.2.1 Preliminaries and notation. . . . .	89
4.2.2 Sampled-data lifted systems. . . . .	91
4.2.3 DRS Frequency Response . . . . .	92
4.3 Frequency Response Interpretation . . . . .	93
4.4 Stability Margins for DRS . . . . .	98
4.4.1 Example. . . . .	99
4.5 Optimum $N$ Determination . . . . .	100
4.5.1 Example 1. . . . .	102
4.5.2 Example 2. . . . .	103
4.6 Conclusions. . . . .	107
References . . . . .	111
5 Paper 4. Delay-independent dual-rate PID controller for a packet- based networked control system	115
5.1 Introduction . . . . .	116
5.2 Problem description . . . . .	120
5.2.1 Time-varying delays, packet dropouts, and packet disorder. . . . .	120
5.2.2 Control structure . . . . .	122
5.3 Control design . . . . .	123
5.3.1 Preliminaries . . . . .	124
5.3.2 Slow-rate PI controller . . . . .	125
5.3.3 Rate converter . . . . .	126
5.3.4 Fast-rate PD controller. . . . .	127
5.3.5 Prediction Stage . . . . .	129

5.4	Stability analysis	130
5.4.1	Closed-loop model via lifting	130
5.4.2	Closed-loop stability	134
5.5	Simulation results	136
5.5.1	Simulation data. Control system stability assessment	136
5.5.2	System responses. Cost indexes $J_1$ and $J_2$	138
5.5.3	Model mismatch. Cost indexes $J_3$ and $J_4$	141
5.6	Experimental results.	144
5.7	Conclusions.	145
	References	149
6	Paper 5. Multirate control strategies for avoiding sample losses. Application to UGV path tracking	155
6.1	Motivation	156
6.2	Problem Statement.	159
6.3	Discrete Lifting Modeling	162
6.3.1	Examples of discrete lifted systems	165
6.4	Dual-rate systems frequency domain	167
6.4.1	DR Systems Frequency Response Computation	167
6.4.2	Frequency Response Interpretation	168
6.4.3	Dual-rate systems quantitative feedback theory	170
6.5	Closed-loop lifted models.	171
6.5.1	Example.	174
6.6	Simulations.	180
6.6.1	Example 1.	180
6.6.2	Example 2.	184
6.7	Experimental Application	188
6.7.1	Path tracking.	189
6.7.2	Dual-rate controller.	189
6.8	Conclusions.	192
	References	195

7 Paper 6. Energy-efficient control for an unmanned ground vehicle in a wireless sensor network	201
7.1 Introduction . . . . .	202
7.2 Problem scenario . . . . .	205
7.2.1 Time-varying network-induced delays, packet dropouts, and packet disorder . . . . .	205
7.2.2 Control structure . . . . .	207
7.3 Energy-efficient control solution design . . . . .	210
7.3.1 Plant modeling . . . . .	210
7.3.2 Event-triggered conditions . . . . .	212
7.3.3 Time-varying dual-rate Kalman filter . . . . .	213
7.3.4 Pure Pursuit path tracking algorithm . . . . .	215
7.3.4.1 Differential kinematics . . . . .	216
7.3.4.2 Path tracking algorithm . . . . .	217
7.3.5 Dual-rate controller . . . . .	220
7.4 Cost indexes for control performance and resource usage . . . . .	222
7.5 Simulation results via Truetime . . . . .	223
7.5.1 Application data . . . . .	223
7.5.2 Truetime simulation and cost function evaluation . . . . .	225
7.6 Conclusions . . . . .	230
References . . . . .	231
8 Paper 7. A remote control strategy for an autonomous vehicle with slow sensor using Kalman filtering and dual-rate control	237
8.1 Introduction . . . . .	238
8.2 Problem Scenario . . . . .	241
8.2.1 Control Structure . . . . .	241
8.2.2 Time-Varying Delays, and Packet Disorder . . . . .	243
8.3 Motion Planning and Control Solution Design . . . . .	246
8.3.1 Plant Modeling . . . . .	246
8.3.1.1 Kinematic Model . . . . .	246
8.3.1.2 Dynamic Model . . . . .	247
8.3.2 Extended Kalman Filter, Including an $h$ -Step-ahead State Prediction Stage . . . . .	248
8.3.3 Pure Pursuit Path Tracking Algorithm . . . . .	251
8.3.4 Dual-Rate Controller . . . . .	253

8.4 Cost Indexes for Control Performance . . . . .	254
8.5 Application . . . . .	255
8.5.1 Data . . . . .	255
8.5.2 Results . . . . .	257
8.6 Conclusions . . . . .	263
References . . . . .	265
9 Conclusions . . . . .	271
9.1 Main contribution . . . . .	271
9.2 Future work . . . . .	273
9.3 Impact factor report . . . . .	275
9.4 Coauthors affiliation . . . . .	281

## List of Figures

1.1	Conventional sampling . . . . .	1
1.2	Asynchronous sampling . . . . .	1
1.3	Multirate sampling . . . . .	2
1.4	Cyclic sampling . . . . .	2
1.5	Random sampling . . . . .	3
1.6	Continuous control (left) and discrete control (right) configurations	3
1.7	Networked control system configuration . . . . .	4
1.8	Problems of NCS: Network access delay (A), Network transmission delay (B), Packet dropout (C), Packet disorder (D), Clock desynchronization (E) and Frequency difference between different clocks (F) . . . . .	5
1.9	Using network only to change reference and to monitor the system	7
1.10	NCS without local control . . . . .	8
1.11	NCS with local open-loop control . . . . .	8
1.12	NCS with local closed-loop control . . . . .	9
1.13	Time-triggered control (left) and event-triggered control (right) configurations . . . . .	11
1.14	TTS transmissions . . . . .	11
1.15	ETS transmissions . . . . .	11

1.16	Periodic event-triggered control configuration . . . . .	12
1.17	PETS transmissions (top) and overstepping the threshold without transmitting data in PETS (bottom) . . . . .	13
1.18	Nominal case (no-delay, no-dropout) . . . . .	14
1.19	Delay-dependent control . . . . .	15
1.20	Delay-independent control . . . . .	15
2.1	Quanser rotary inverted pendulum . . . . .	34
2.2	Top and front view . . . . .	35
2.3	Control structure in ideal conditions . . . . .	36
2.4	Theta and alpha angles: T=10ms . . . . .	37
2.5	Theta and alpha angles: T=15 ms . . . . .	38
2.6	Threshold-based communication flowchart . . . . .	40
2.7	Theta threshold . . . . .	42
2.8	Alpha threshold . . . . .	42
2.9	Control action threshold . . . . .	43
2.10	Performance index . . . . .	43
2.11	Theta and alpha thresholds . . . . .	44
2.12	Theta and control thresholds . . . . .	45
2.13	Alpha and control thresholds . . . . .	45
2.14	Theta and alpha: Threshold control . . . . .	46
2.15	Theta angle: Captured and transmitted . . . . .	47
2.16	Theta transmission flag . . . . .	48
3.1	NCS scenario . . . . .	60
3.2	Prediction stage in detail . . . . .	62

3.3	No packet dropout ( $d_k^{r_l} = 1$ ) . . . . .	63
3.4	Packet dropout ( $d_k^{r_l} = 0$ ) . . . . .	64
3.5	Cartesian robot (3D CRANE module) . . . . .	75
3.6	Delay histogram . . . . .	76
3.7	Simulation results: nominal vs delay-dependent with packet dropouts and no prediction vs delay-dependent with packet dropouts with prediction . . . . .	77
3.8	Experimental results: nominal vs delay-dependent with packet dropouts and no prediction vs delay-dependent with packet dropouts with prediction . . . . .	80
4.1	Generalized Dual-Rate System . . . . .	90
4.2	Kranc's vector switch decomposition . . . . .	91
4.3	DRS Bode . . . . .	94
4.4	DRS Bode Interpretation. $w = 3R/s$ . . . . .	95
4.5	DRS Bode. $w = 3R/s$ . Zoom . . . . .	95
4.6	Output Components Sum Comparison . . . . .	96
4.7	DRS Bode. Comparison of Methods . . . . .	96
4.8	DRS Bode. Comparison of Methods . . . . .	97
4.9	Output Components Sum at $T_0$ Comparison . . . . .	98
4.10	Simulation Diagram. Case $N_y = 3$ . . . . .	99
4.11	$T_0$ Bode Stability Margins Determination . . . . .	100
4.12	Simulation of DRS with Stability Margins consideration . . . . .	101
4.13	Metaperiod $T_0$ DRS Bode and the greatest Singular Value . . . . .	101
4.14	DR control scheme applied in example 1 . . . . .	102
4.15	Time Response for different values of $N$ . . . . .	103

4.16	Root Locus for different values of $N$ . . . . .	104
4.17	Open Loop Bode diagrams for different values of $N$ . . . . .	104
4.18	Closed Loop Bode diagrams for different values of $N$ . . . . .	105
4.19	Closed Loop Dual-Rate Control. Non-conventional Dual-Rate Controller Structure used in example 2 . . . . .	106
4.20	Time Response for different values of $N$ . . . . .	107
4.21	Root Locus for different values of $N$ . . . . .	107
4.22	Open Loop Bode diagrams for different values of $N$ . . . . .	108
4.23	Closed Loop Bode diagrams for different values of $N$ . . . . .	108
5.1	NCS scenario . . . . .	120
5.2	Packet dropout ( $d_k^{rl} = 0$ ) . . . . .	124
5.3	No packet dropout ( $d_k^{rl} = 1$ ) . . . . .	124
5.4	Cartesian robot (3D CRANE module) . . . . .	136
5.5	Delay histogram . . . . .	138
5.6	Comparison: nominal vs no prediction vs delay-dependent vs delay-independent . . . . .	139
5.7	Comparison: nominal vs delay-independent (model mismatch) . . . . .	142
5.8	Comparison: nominal vs no prediction vs delay-dependent vs delay-independent . . . . .	145
5.9	Comparison (Lissajous curves): nominal vs no prediction vs delay-dependent vs delay-independent . . . . .	146
6.1	Fast digital control . . . . .	159
6.2	Dual-rate inferential control . . . . .	160
6.3	Model-based dual-rate control . . . . .	161
6.4	Generalized dual-rate system . . . . .	162

6.5	Kranc vector switch decomposition. General case . . . . .	163
6.6	Y/R MBDR lifted process . . . . .	172
6.7	Y/R IC lifted process . . . . .	173
6.8	Y/d MBDR lifted process . . . . .	177
6.9	Y/d IC lifted process . . . . .	180
6.10	Example 1. Time response without MPM . . . . .	182
6.11	Example 1. Time response with MPM . . . . .	182
6.12	Example 1. Y/R DR systems Bode. Methods comparison . . . . .	183
6.13	Example 1. MBDR case QFT analysis . . . . .	183
6.14	Example 1. IC case QFT analysis . . . . .	184
6.15	Disturbance rejection comparison . . . . .	184
6.16	Example 2. Time response without MPM . . . . .	185
6.17	Example 2. Time response with MPM . . . . .	186
6.18	Example 2. Y/R DR systems Bode. Methods comparison . . . . .	186
6.19	Example 2. IC case QFT analysis . . . . .	187
6.20	Example 2. MBDR case QFT analysis . . . . .	187
6.21	Autonomous robot used . . . . .	188
6.22	UGV QFT analysis . . . . .	191
6.23	UGV Path tracking . . . . .	191
6.24	UGV. Linear and Non-linear servomotors comparison . . . . .	192
7.1	Energy-efficient control system for a WSN . . . . .	206
7.2	Structure of the Time-Varying Dual-Rate Kalman Filter . . . . .	214
7.3	Circumference between current point and target point . . . . .	217
7.4	Structure of the Pure Pursuit path tracking algorithm . . . . .	219

7.5	Structure of the dual-rate controller . . . . .	221
7.6	Time-triggered single-rate control at period $NT$ (no noise, no disturbance, no delays, no dropouts) . . . . .	225
7.7	Time-triggered single-rate control at period $T$ (no noise, no disturbance, no delays, no dropouts). Nominal performance . . . . .	226
7.8	Time-triggered dual-rate control (no noise, no disturbance, no delays, no dropouts) . . . . .	226
7.9	Time-triggered dual-rate control (no noise, no disturbance, delays, dropouts) . . . . .	227
7.10	Time-triggered dual-rate control, with TVDRKF, and packet-based control (noise, disturbance, delays, dropouts) . . . . .	227
7.11	Disturbance estimation by TVDRKF . . . . .	228
7.12	Periodic event-triggered dual-rate control, with TVDRKF, and packet-based control (noise, disturbance, delays, dropouts) . . . . .	228
8.1	Remote control structure for an autonomous vehicle . . . . .	241
8.2	Time axis example for the remote-to-local channel . . . . .	244
8.3	Time axis example for the local-to-remote channel . . . . .	245
8.4	Lego robot . . . . .	256
8.5	Results for the single-rate control at $T = 0.1$ s . . . . .	258
8.6	Results for the single-rate control at $NT = 0.2$ s . . . . .	258
8.7	Results for the dual-rate control at $NT = 0.2$ s and $T = 0.1$ s . . . . .	259
8.8	Results for the dual-rate control with delays . . . . .	259
8.9	Results for the control proposal (EKF, prediction stage, and packet-based control) with delays and a lower level of noise . . . . .	260
8.10	Control signal for the control proposal (EKF, prediction stage, and packet-based control) with delays and a lower level of noise . . . . .	260

8.11	Results for the control proposal (EKF, prediction stage, and packet-based control) with delays and a higher level of noise . . .	261
8.12	Control signal for the control proposal (EKF, prediction stage, and packet-based control) with delays and a higher level of noise	262
9.1	First page of paper 1 published in ISA Transactions . . . . .	275
9.2	First page of paper 2 published in ISA Transactions . . . . .	276
9.3	First page of paper 3 published in International Journal of General Systems . . . . .	276
9.4	First page of paper 4 published in Information Sciences . . . . .	277
9.5	First page of paper 5 published in ISA Transactions . . . . .	277
9.6	First page of paper 6 published in Journal of Sensors . . . . .	278
9.7	First page of paper 7 published in Sensors . . . . .	279



## List of Tables

2.1	Alpha and control action thresholds . . . . .	48
3.1	Cost indexes $J_1$ and $J_2$ in simulation . . . . .	79
3.2	Cost indexes $J_1$ and $J_2$ in experimentation . . . . .	80
5.1	Simulation: accumulated error $E_Y$ and cost index $J_1$ ; overshoot $O_Y$ and cost index $J_2$ . . . . .	141
5.2	Accumulated error $E_W$ and cost index $J_3$ . . . . .	143
5.3	Overshoot $O_W$ and cost index $J_4$ . . . . .	143
5.4	Experiment: accumulated error $E_Y$ and cost index $J_1$ ; overshoot $O_Y$ and cost index $J_2$ . . . . .	144
7.1	Cost indexes . . . . .	229
8.1	Example for $h = 1$ . . . . .	261
8.2	Cost indexes for each scenario . . . . .	262
9.1	Quality metrics of the publications. . . . .	280