

TABLA DE CONTENIDOS

I. INTRODUCCIÓN.....	1
I.1. Polímeros de alto rendimiento medioambiental.	3
I.1.1. Polímeros termoplásticos	3
I.1.2. Polímeros termoestables	15
I.2. Tecnología del poli(ácido láctico).....	23
I.2.1. Obtención del poli(ácido láctico).....	24
I.2.2. Propiedades generales del poli(ácido láctico).....	26
I.2.3. Tecnologías de modificaciones del poli(ácido láctico)	29
I.2.4. Compuestos con base de poli(ácido láctico).....	33
I.3. Tecnologías de compuestos de resina epoxi de origen renovable	52
I.3.1. Triglicéridos y aceites vegetales.....	53
I.3.2. Modificación de aceites vegetales	55
I.3.3. Cinética de entrecruzamiento	62
I.3.4. Materiales compuestos de alto rendimiento medioambiental con matrices termoestables	77
I.4. Referencias.....	81
II. OBJETIVOS	99
II.1. Objetivo General	101
II.2. Objetivos Específicos	101
III. RESULTS AND DISCUSSION.....	105
III.1. Blends and composites with thermoplastic matrices of high environmental performance	109
III.1.1. Toughened poly (lactic acid)-PLA formulations by binary blends with poly(butylene succinate-co-Adipate)-PBSA and their shape memory behaviour	111
III.1.2. Development of injection-molded polylactide pieces with high toughness by the addition of lactic acid oligomer and characterization of their shape memory behavior	137
III.1.3. Manufacturing and characterization of highly environmentally friendly sandwich composites from polylactide cores and flax-polylactide faces.....	167
III.1.4. A comparative study of mechanical properties of polylactide bio-composites with woven and non-woven jute reinforcements.....	193
III.2. Composites based on thermosetting matrices with high environmental performance.	219

III.2.1. Kinetic analysis of the curing of a partially biobased epoxy resin using dynamic differential scanning calorimetry	221
III.2.2. Kinetic analysis of the curing process of biobased epoxy resin from epoxidized linseed oil by dynamic differential scanning calorimetry	257
III.2.3. Optimization of the curing and post-curing conditions for the manufacturing of partially bio-based epoxy resins with improved toughness	285
III.2.4. Manufacturing and characterization of green composites with partially biobased epoxy resin and flaxseed flour wastes	313
III.2.5. Manufacturing and characterization of hybrid composites with basalt and flax fabrics and a partially bio-based epoxy resin	351
III.2.6. Manufacturing of composite materials with high environmental efficiency using epoxy resin of renewable origin and permeable light cores for vacuum-assisted infusion molding	383
IV. CONCLUSIONES	403
IV.1. Conclusiones Parciales	405
IV.1.1. Mezclas y compuestos con matrices termoplásticas con alto rendimiento medioambiental	405
IV.1.2. Compuestos con matrices termoestables con alto rendimiento medioambiental	406
IV.2. Conclusiones generales	407