

---

# Contents

---

<b>Abstract</b>	vii
<b>Resumen</b>	ix
<b>Resum</b>	xi
<b>List of acronyms</b>	1
<b>1 Introduction</b>	3
1.1 Motivation and background . . . . .	5
1.2 Objectives . . . . .	6
1.3 Organization and development of the Thesis . . . . .	7
<b>2 Fundamentals: modelling of acoustic problems and optimization techniques</b>	11
2.1 The acoustic problem . . . . .	13
2.1.1 Introduction . . . . .	13
2.1.2 Models for the acoustic calculation . . . . .	13
2.1.2.1 Dynamic model . . . . .	13
2.1.2.2 Linear acoustic model . . . . .	15
2.1.3 Wave equation . . . . .	16
2.1.3.1 Non-moving medium . . . . .	18
2.1.3.2 Moving medium . . . . .	19
2.1.4 One-dimensional acoustics of ducts . . . . .	20
2.1.4.1 Non-moving medium . . . . .	20
2.1.4.2 Moving medium . . . . .	21
2.1.5 Plane wave models. Matrix representations . . . . .	22
2.1.5.1 Generalities . . . . .	23
2.1.5.2 Transfer matrix of a duct . . . . .	24
2.1.5.3 Transfer matrix at expansions and contractions	26
2.2 The fluid-structure interaction problem . . . . .	27
2.2.1 Displacement/pressure mixed formulation in 2D . . . . .	29
2.3 Structural shape optimization . . . . .	30

---

2.3.1	Introduction . . . . .	30
2.3.2	Optimization algorithms . . . . .	31
2.3.2.1	Method of moving asymptotes (MMA) . . . . .	32
2.3.2.2	Sensitivity analysis . . . . .	33
2.3.2.3	Genetic algorithms . . . . .	35
2.3.3	Topology optimization . . . . .	37
2.3.3.1	Material interpolation schemes . . . . .	38
<b>3</b>	<b>Acoustic optimization of dissipative and hybrid mufflers</b>	<b>39</b>
3.1	Introduction . . . . .	41
3.1.1	Classification of mufflers . . . . .	41
3.1.1.1	Reactive configuration . . . . .	41
3.1.1.2	Dissipative configuration . . . . .	42
3.1.2	Optimization of mufflers . . . . .	42
3.1.2.1	Optimization of reactive mufflers . . . . .	42
3.1.2.2	Optimization of dissipative and hybrid mufflers	43
3.2	Acoustic modelling of reactive and dissipative mufflers . . . . .	44
3.2.1	Previous considerations: perforated ducts and absorbing materials . . . . .	44
3.2.1.1	Characteristic impedance of a perforated surface	44
3.2.1.2	Absorbent materials . . . . .	47
3.2.2	Finite element method . . . . .	48
3.2.2.1	Wave propagation along the central passage domain $\Omega_a$ . . . . .	50
3.2.2.2	Wave propagation in the dissipative chamber $\Omega_m$ . . . . .	52
3.2.2.3	Acoustic coupling at the perforated duct . . . . .	53
3.2.2.4	Boundary conditions at the outlet . . . . .	54
3.2.2.5	Final system of equations . . . . .	55
3.3	Objective Function: Transmission loss . . . . .	55
3.4	Optimization problem . . . . .	57
3.5	Results . . . . .	58
3.5.1	Temperature distribution . . . . .	58
3.5.2	Multi-frequency topology optimization of a dissipative muffler . . . . .	59
3.5.2.1	Design 1. Cold condition optimization. Low frequency range . . . . .	60
3.5.2.2	Design 1a. Manufacturable muffler with $\rho_b = 50 \text{ kg/m}^3$ and extended ducts . . . . .	61

---

3.5.2.3	Results discussion. Designs 1 and 1a . . . . .	62
3.5.2.4	Design 2. Cold condition optimization. Mid frequency range . . . . .	62
3.5.2.5	Design 2a. Manufacturable muffler with a ring design . . . . .	64
3.5.2.6	Design 2b. Manufacturable muffler with a ring design and extended ducts . . . . .	65
3.5.2.7	Design 3. Operating (hot) condition optimization. Middle frequency range . . . . .	65
3.5.2.8	Results discussion. Designs 2, 2a, 2b and 3 . .	66
3.5.3	Multi-frequency shape optimization of a hybrid muffler with multiple constraints . . . . .	69
3.5.3.1	Design 4. Broad frequency range . . . . .	69
3.5.3.2	Results discussion. Design 4 . . . . .	70
3.6	Conclusions . . . . .	72
<b>4</b>	<b>Acoustic optimization of exhaust aftertreatment devices</b>	<b>73</b>
4.1	Introduction . . . . .	75
4.2	Acoustic modelling of aftertreatment devices . . . . .	75
4.2.1	Catalytic converter . . . . .	76
4.2.1.1	1-D acoustic modelling of the monolith . . . . .	77
4.2.2	Diesel particulate filters . . . . .	79
4.2.2.1	The 1-D wave model . . . . .	80
4.2.2.2	The in- and oulet sections (IN+I and III+OUT) .	81
4.2.2.3	The filter section (II) . . . . .	82
4.2.3	Modal expansion method . . . . .	84
4.2.4	Mode matching technique . . . . .	85
4.2.4.1	Mode matching at the device expansion . . . . .	85
4.2.4.2	Transfer matrix of the monolith . . . . .	86
4.2.4.3	Mode matching at the device contraction . . . . .	87
4.2.4.4	Final system of equations . . . . .	87
4.3	Objective function: Transmission loss . . . . .	88
4.4	Optimization problem . . . . .	88
4.5	Results . . . . .	88
4.5.1	Design 1. Shape optimization of a catalytic converter .	89
4.5.1.1	Influence of duct offsets . . . . .	91
4.5.2	Design 2. Shape optimization of a diesel particulate filter	93
4.6	Conclusions . . . . .	98

---

<b>5 Topology optimization of fluid-structure problems</b>	<b>101</b>
5.1 Introduction . . . . .	103
5.2 Vibroacoustic modelling of a fluid-structure interaction problem	104
5.2.1 Mixed finite element method in $\Omega_d$ . . . . .	105
5.2.2 Helmholtz equation in $\Omega_a$ . . . . .	106
5.2.3 Subdomain coupling . . . . .	108
5.2.4 Absorbing boundary $\Gamma_o$ . . . . .	109
5.3 Two-material interpolation schemes of vibroacoustic properties	109
5.4 Objective function . . . . .	111
5.4.1 Acoustic contribution . . . . .	111
5.4.2 Static load case . . . . .	112
5.5 Optimization problem . . . . .	112
5.5.1 Stopping criteria . . . . .	113
5.6 Results . . . . .	113
5.6.1 Material properties . . . . .	113
5.6.2 Design 1. Duct screen . . . . .	114
5.6.3 Design 2. Duct shielding . . . . .	116
5.6.4 Design 3. Train fairing . . . . .	120
5.7 Conclusions . . . . .	123
<b>6 Conclusions</b>	<b>125</b>
<b>7 Further publications</b>	<b>129</b>
7.1 International journals (JCR) . . . . .	129
7.2 National congresses . . . . .	129
7.3 International congresses . . . . .	130
<b>Bibliography</b>	<b>133</b>