

Table of contents

| | |
|---|------------|
| List of Figures | vii |
| List of Tables | x |
| Acronyms | xi |
| Notation | xvi |
| 1 Introduction | 1 |
| 1.1 Background - When 5G and AI Meet | 1 |
| 1.1.1 5G Mobile: The New Generation and the Future of Wireless Communications | 3 |
| 1.1.2 Release 15 | 5 |
| 1.1.3 Release 16 | 8 |
| 1.1.4 Release 17 | 9 |
| 1.1.5 Release 18 | 10 |
| 1.1.6 5G Use Cases | 12 |
| 1.1.7 Cooperative Agents in Industry 4.0: Transforming the Future with the AI | 15 |
| 1.1.8 Challenges in AI | 23 |
| 1.2 Problem and Thesis Scope | 25 |
| 1.3 Thesis Objectives | 27 |
| 1.4 Thesis Outline | 29 |
| 1.5 Thesis Publications | 30 |
| 2 Simulation Tools and Navigation: A Comparative Analysis | 31 |
| 2.1 Robot Operating System | 31 |
| 2.1.1 ROS Melodic and Main Concepts | 33 |
| 2.2 Simulator Gazebo | 35 |
| 2.2.1 Build a Model | 35 |

TABLE OF CONTENTS

| | | |
|----------|---|-----------|
| 2.3 | Communication between Gazebo & ROS | 38 |
| 2.4 | Exploring Navigation: SLAM vs. RL Comparative Analysis | 38 |
| 2.4.1 | Simultaneous Localization and Mapping (SLAM) | 38 |
| 2.4.2 | SLAM vs. RL Approach applied to Navigation | 40 |
| 3 | Path Planning Algorithms | 42 |
| 3.1 | Path Planning Background | 42 |
| 3.1.1 | Traditional Path Planning Approaches | 43 |
| 3.1.2 | Machine Learning Path Planning Approaches | 48 |
| 3.2 | Machine Learning | 50 |
| 3.2.1 | Markov Decision Process | 50 |
| 3.2.2 | Reinforcement Learning | 52 |
| 3.3 | How to Design a Path Planning Algorithm by RL | 55 |
| 3.3.1 | Action Space | 55 |
| 3.3.2 | Reward Space | 58 |
| 3.3.3 | Observation Space | 65 |
| 3.4 | Results Discussion | 73 |
| 3.4.1 | Comparison of the Area Discovered in Environment 1 . | 73 |
| 3.4.2 | Comparison of the Area Discovered in Environment 2 . | 74 |
| 3.4.3 | Comparison of Time and Distance Traveled to Reach a Target in Environment 1 | 76 |
| 3.4.4 | Comparison of Time and Distance Traveled to Reach a Target in Environment 2 | 76 |
| 3.4.5 | Comparison of the Number of Targets Reached per Episode in Environment 1 | 79 |
| 3.4.6 | Comparison of the Number of Targets Reached per Episode in Environment 2 | 79 |
| 3.4.7 | Evolution of the Performance of the Algorithms in Environment 1 | 80 |
| 3.4.8 | Evolution of the Performance of the Algorithms in Environment 2 | 81 |
| 3.5 | Conclusions | 82 |
| 4 | Data Management and Vommunications in Motion Planning | 84 |
| 4.1 | Overview of 5G Specifications | 85 |
| 4.2 | The Role of Artificial Intelligence | 86 |
| 4.2.1 | Types of Data | 88 |
| 4.3 | Arquitectures | 89 |
| 4.4 | Analysis of Computing Resources for the Different Architectures | 91 |
| 4.5 | Analysis of Network Requirements as the Number of Agents Increases | 93 |

TABLE OF CONTENTS

| | | |
|-------------------|---|------------|
| 4.6 | How to Design a Data Homogenization Algorithm | 96 |
| 4.6.1 | Data Homogenization | 96 |
| 4.6.2 | Data Synchronization | 98 |
| 4.6.3 | Estimation of Unknown Data | 102 |
| 4.7 | Results Discussion | 111 |
| 4.8 | Conclusions | 118 |
| 5 | Multi Robot Cooperation | 120 |
| 5.1 | Multi-Agent Path Planning Background | 121 |
| 5.2 | Learning Methods | 123 |
| 5.2.1 | Independent Learning | 123 |
| 5.2.2 | Joint Action Learning | 124 |
| 5.3 | Learning Algorithm | 125 |
| 5.3.1 | Deep Deterministic Policy Gradient (DDPG) | 125 |
| 5.4 | How to Design a Cooperative Algorithm using DRL | 125 |
| 5.4.1 | Architecture | 126 |
| 5.4.2 | Modification of JAL | 127 |
| 5.4.3 | Self-advice Module | 130 |
| 5.4.4 | k-Nearest Neighbors Algorithm | 130 |
| 5.5 | Results Discussion | 138 |
| 5.5.1 | Performance during the Training Phase | 139 |
| 5.5.2 | Evaluation of the Interaction between Agents | 140 |
| 5.5.3 | Performance of the Trained Policy | 143 |
| 5.6 | Conclusions | 146 |
| 6 | Conclusions and Future Work | 148 |
| 6.1 | Concluding Remarks | 148 |
| 6.2 | Future Research Lines | 153 |
| References | | 155 |

List of Figures

| | | |
|------|---|----|
| 1.1 | Where 5G and AI meet | 2 |
| 1.2 | Five generations of telecommunications | 3 |
| 1.3 | 5G requirements defined by ITU-R | 6 |
| 1.4 | 5G use case scenarios | 7 |
| 1.5 | Requirements and standardization of IIoT | 9 |
| 1.6 | Release 17 - RedCap | 10 |
| 1.7 | 5G NR and 5GC | 11 |
| 1.8 | 3GPP Release 18 features | 11 |
| 1.9 | 3GPP evolution of 5G | 12 |
| 1.10 | Factory 5G use cases | 14 |
| 1.11 | Four industrial revolution | 15 |
| 1.12 | Can machines think? | 17 |
| 1.13 | Perceptron diagram | 18 |
| 1.14 | AI revolution | 19 |
| 1.15 | Subfields of AI and ML | 21 |
| 1.16 | Industry and RL | 22 |
| 1.17 | Challenges in AI | 24 |
| 2.1 | Melodic ROS distribution | 33 |
| 2.2 | TurtleBot3 nodes | 34 |
| 2.3 | Main components in ROS | 34 |
| 2.4 | Design of 3D scenarios | 35 |
| 2.5 | Parts of gazebo simulator | 36 |
| 2.6 | Gazebo simulator. | 37 |
| 2.7 | Melodic ROS distribution. | 38 |
| 2.8 | Example of simultaneous localization and mapping. | 39 |
| 3.1 | Classification algorithms for path planning | 43 |
| 3.2 | Algorithm A* | 46 |

LIST OF FIGURES

| | | |
|------|--|-----|
| 3.3 | Genetic algorithm | 47 |
| 3.4 | Example of an MPI | 51 |
| 3.5 | Elements of the RL | 52 |
| 3.6 | Q-L algorithm | 53 |
| 3.7 | Illustration of DRL | 54 |
| 3.8 | Actions that the agent can perform | 56 |
| 3.9 | Illustration of reward types | 59 |
| 3.10 | Heat map of designed rewards | 61 |
| 3.11 | Agent rewards based on the heading | 61 |
| 3.12 | Agent's orientation towards the target | 62 |
| 3.13 | Example of the path traced by the agent | 64 |
| 3.14 | Environment 2 ("Turtlebot3_plaza") | 65 |
| 3.15 | Agent vision regions | 66 |
| 3.16 | Discovered area of the first environment | 74 |
| 3.17 | Discovered area of the second environment | 75 |
| 3.18 | Comparison of time and distance traveled | 77 |
| 3.19 | Comparison of targets reached | 78 |
| 3.20 | Success rate vs. collisions | 80 |
| 4.1 | Classification of the multi-robot system | 87 |
| 4.2 | Decentralized architecture | 89 |
| 4.3 | Semi-decentralized architecture | 90 |
| 4.4 | Centralized architecture | 91 |
| 4.5 | Performance | 92 |
| 4.6 | Throughput requirements for 50 agents | 94 |
| 4.7 | Throughput requirements for 500 agents | 94 |
| 4.8 | Latency | 95 |
| 4.9 | Laser vision split into 24 scans | 97 |
| 4.10 | Map of the 24 scans obtained with a camera of 90 | 99 |
| 4.11 | Synchronization and sorting process | 101 |
| 4.12 | Data estimation for linear motion | 104 |
| 4.13 | Data estimation for angular motion | 106 |
| 4.14 | Data estimated for back values | 108 |
| 4.15 | Interpolated data | 109 |
| 4.16 | Process of interpolation | 110 |
| 4.17 | Success rate for each goal | 112 |
| 4.18 | Performance obtained by a camera | 113 |
| 4.19 | Performance of load model 90° - 5 min | 114 |
| 4.20 | Performance of the load model 90° - 60 min | 115 |
| 4.21 | Performance of the load model 360° - 5 min | 116 |
| 4.22 | Performance of the load model 360° - 60 min | 116 |

LIST OF FIGURES

| | | |
|------|--|-----|
| 5.1 | Illustration of IL | 123 |
| 5.2 | Illustration of JAL | 124 |
| 5.3 | Semi-decentralized architecture (MARL) | 127 |
| 5.4 | Modification of JAL | 128 |
| 5.5 | k-nearest neighbors algorithm | 130 |
| 5.6 | First environment | 135 |
| 5.7 | Second environment | 137 |
| 5.8 | Architecture of the proposed algorithm | 138 |
| 5.9 | Ratio of success rate in the first environment | 139 |
| 5.10 | Ratio of success rate in the second environment | 141 |
| 5.11 | Evaluation of the interaction between agents in the first environment | 142 |
| 5.12 | Evaluation of the interaction between agents in the second environment | 144 |
| 5.13 | Team performance obtained when agents start from the same point | 145 |
| 5.14 | Team performance obtained in the first environment | 145 |
| 5.15 | Team performance obtained in the second environment | 146 |

List of Tables

| | | |
|-----|--|-----|
| 2.1 | Comparative navigation using SLAM and RL | 41 |
| 3.1 | Velocities assigned to each action | 56 |
| 3.2 | Summary of reward metrics | 63 |
| 3.3 | Summary of the reward for the path traveled | 64 |
| 3.4 | Summary of the key parameters of the algorithm | 68 |
| 3.5 | Summary of episodes and training time | 81 |
| 3.6 | Success rate | 82 |
| 4.1 | Parameters for latency analysis | 95 |
| 4.2 | Configuration of the sensors used | 101 |
| 4.3 | Main characteristics of the sensors | 102 |
| 4.4 | Summary of the medians | 117 |
| 5.1 | Velocity corresponding to the actions | 135 |