

Photonic Vector Processing Techniques for Radiofrequency Signals

MIGUEL ÁNGEL PIQUERAS RUIPÉREZ

SUPERVISORS:

DR. JUAN LUIS CORRAL GONZÁLEZ

DR. BORJA VIDAL RODRÍGUEZ



UNIVERSITAT
POLITÈCNICA
DE VALÈNCIA

Departamento de Comunicaciones
UNIVERSIDAD POLITÉCNICA DE VALENCIA
Valencia, December 2015

Table of Contents

ABSTRACT	1
LIST OF PUBLICATIONS INCLUDED IN THE THESIS	8
PUBLICATIONS IN INTERNATIONAL JOURNALS	8
CONTRIBUTIONS TO INTERNATIONAL CONGRESS	9
PATENTS	11
1. INTRODUCTION TO PHOTONIC TECHNOLOGY	1
1.1. Fibre-optic Systems	2
1.2. Photonic Integrated Circuits (PIC)	6
1.3. Microwave Photonics	8
1.4. Microwave Photonic Links	10
1.4.1. Carrier-to-noise Ratio	19
1.4.1.1. Thermal noise	20
1.4.1.2. Shot noise	20
1.4.1.3. RIN noise	20
1.4.1.4. EDFA noise	21
1.5. Photonic Up and Down Conversion	23
1.6. Vector Microwave Optical Processing	25
1.6.1. Optical Beamforming Networks	25
1.6.2. Photonic Vector Modulator for Communications	27
2. OPTICAL BEAMFORMING NETWORKS	29
2.1. Introduction to Antenna Theory	29
2.1.1. Scanning and Collimation of Linear and Planar Arrays	30
2.1.2. Bandwidth	31
2.1.3. Time-Delay Compensation	32
2.1.4. Multiple Beam Array Feeds	34
2.1.5. Control for Wideband Arrays	37
2.2. Review of Optical Beamforming Networks	39

2.2.1.	Antenna Beamforming Networks	39
2.2.2.	True Time-Delay Optical Beamforming	42
2.2.2.1.	Free-space and semi-guided-wave optical delay line beamformers	42
2.2.2.2.	Fibre-optic delay line beamformers	44
2.2.2.3.	WDM beamformers based on Dispersion Fibre Prism, Fibre Bragg Gratings and Wavelength Multiplexers	46
2.2.2.4.	Integrated-optics delay line beamformers	51
2.2.2.5.	Phase-shifting coherent optical beamformers	52
2.2.2.6.	Free-space Fourier transform optical signal processors (OSP)	53
2.2.2.7.	Hybrid SLM-based coherent beamformers	53
2.2.2.8.	Optical coherent beamformer based on integrated phase-shifters	54
2.3.	Conclusion	56
3.	PHOTONIC SWITCHED BEAMFORMER FOR BROADBAND WIRELESS ACCESS	60
3.1.	Beamformer Architecture Description	61
3.1.1.	Transmission Mode.....	61
3.1.2.	Reception Mode	62
3.1.3.	TTD 2×2 switching matrix	64
3.2.	Time Delay Calibration.....	64
3.3.	System Performance Analysis.....	66
3.3.1.	Laser RIN	67
3.3.2.	System Electrical Bandwidth	67
3.3.3.	Required Modulation Index.....	68
3.3.4.	1dB Compression Point.....	69
3.3.5.	Wavelength Stability	70
3.4.	Experimental Results.....	71
3.4.1.	Transmission Mode.....	71
3.4.2.	Reception Mode	74
3.5.	On the Capability of Multi beam Operation	77
3.5.1.	Architecture Description	77
3.5.2.	Experimental Results	78
3.6.	Conclusion	80
4.	DIRECTION OF ARRIVAL ESTIMATION OF BROADBAND SIGNALS IN PHASED ARRAYS BY PHOTONIC PROCESSING.....	81

4.1. Principle of Operation	82
4.2. Architecture Description	83
4.3. Experimental Results.....	86
4.4. Conclusion	91
5. HETERODYNE OBFN BASED ON INTEGRATED BUTLER MATRICES	92
5.1. Application Scenario.....	93
5.2. Optical Butler Matrices for Electrical Beamforming	96
5.2.1. Principle of Operation: Heterodyne Phase Shifting	97
5.3. 2N Beam Directions with a NxN Optical Butler Matrix	99
5.4. Design of an Integrated Optical Butler Matrix	100
5.4.1. The Optical Butler Matrix	100
5.5. 8x8 Butler Matrix Fabrication	110
5.6. Characterization of the 8x8 Butler Matrix	111
5.6.1. Optical Insertion Losses.....	111
5.6.2. Phase Shift Performance of a 8x8 Butler Matrix	112
5.7. Impact of experimental results on System Performance	114
5.8. Distribution Input Matrix	116
5.8.1. DIM structures and sample characterization	116
5.8.2. Results on Phase Distribution	118
5.9. Conclusion	120
6. RF-LIKE OBFN BASED ON INTEGRATED OPTICAL BUTLER MATRICES.....	121
6.1. Design of the RF-Like Optical Butler	123
6.1.1. Basic Optical Coupler Equivalent to 2x2 Hybrid RF Coupler or 2x2 Butler Matrix	123
6.1.2. 4x4 Optical Butler Matrix.....	123
6.1.3. 8x8 Optical Butler Matrix.....	125
6.2. RF-Like 8x8 Optical Butler PIC manufacturing	128

6.3. RF-Like 8x8 Optical Butler PIC Evaluation.....	131
6.3.1. Insertion Loss Performance.....	131
6.3.2. Polarization and Wavelength Dependence.....	132
6.3.3. Phase Shifting Performance of the Matrix.....	133
6.4. Conclusion	134
7. PHOTONIC MICROWAVE SIGNAL GENERATION.....	135
7.1. Introduction	135
7.2. Photonic generation of wireless signals.....	136
7.3. Fundamentals of Quadrature Modulations.....	138
7.3.1. QAM Theory and Formulas	139
7.3.2. QAM Modulator & Demodulator.....	140
8. PHOTONIC GENERATION OF ELECTRICAL VECTOR MODULATIONS AT MICROWAVE/MILLIMETRE-WAVE FREQUENCIES.....	142
8.1. Photonic Vector QPSK Modulator Architecture.....	142
8.1.1. Performance Analysis.....	144
8.1.2. Experimental Results.....	145
8.2. Photonic Vector QAM Modulator Architecture	148
8.2.1. Experimental Results.....	149
8.3. Conclusion	151
9. SIMULTANEOUS BASE-BAND AND MM-WAVE DELIVERY OF GB/S DATA EMPLOYING PHOTONIC VECTOR MODULATORS	152
9.1. Scenario Description	153
9.1.1. Application Scenario 1: Point-to-point Fixed Wireless Access (FWA) connections	153
9.1.2. Application Scenario 2: Coverage extension via wireless of fibre-to-the-home	154
9.1.3. Application Scenario 3: Uncompressed HD video transmission	155
9.2. Architecture Description and Experimental Setup	156
9.3. Experimental Measurements.....	157

9.4. Photonic Integrated Circuit implementing a Heterodyne Photonic Vector Modulator	159
9.4.1. Mathematical Model.....	160
9.4.2. Discussion	162
10. PHOTONIC VECTOR DEMODULATION ARCHITECTURE FOR REMOTE DETECTION OF M-QAM SIGNALS	163
10.1. Architecture Description.....	163
10.2. Performance Analysis	166
10.3. Simulation Results	167
10.4. Experimental Results for QPSK modulations	169
10.5. Conclusion.....	172
11. CONCLUSION	173
12. REFERENCES	175
13. ANNEX A: IMPACT OF ELEMENT FAILURES IN AN OPTICAL BUTLER MATRIX	190
A.1 Basic formulas for the effect of errors in large antenna arrays	190
14. ANNEX B: FABRICATION PROCESS IN SOI	193
Spin Coating.....	194
Exposure.....	194
Developing	196
Etching process.....	196
15. ANNEX C: ANALYTICAL MODEL OF THE PHOTONIC VECTOR MODULATOR	203
C.1. Simplified PVM model	203

C.2. Noise analysis	208
C.3. Complete PVM model with a second-order dispersive link (QB biasing).....	210
C.4. Complete model with a second-order dispersive link (MATB biasing)	215
C.5. Simplified PVM model without LO leakage	217
C.6. Complete 3-lasers PVM model including a second-order dispersive link (QB biasing)	220