"Contribution to the understanding of filtration and pressure drop phenomena in wall-flow DPFs"

Presented by: D. EMANUELE ANGIOLINI

Supervised by: DR. D. PEDRO PIQUERAS CABRERA

Contents

List of Figures

List of Tables

Nomenclature

1 Introduction

- 1.1 Background
- 1.2 Motivation of the study
- 1.3 Objectives
- 1.4 Methodology
- 1.5 References

2 Background and state of the art

- 2.1 Introduction
- 2.2 Wall-flow DPF modelling in OpenWAM™
- 2.3 Filtration models
- 2.4 DPF design criteria
- 2.5 Pre-turbo aftertreatment placement
- 2.6 Pre-DPF water injection technique
- 2.7 Summary
- 2.8 References

3 Wall-flow PF filtration model

- 3.1 Introduction
- 3.2 Species transport equation
- 3.3 Filtration Mechanisms
- 3.4 Filtration regimes
- 3.5 Pulsating flow effect

- 3.6 Soot distribution for water injection modelling
- 3.7 Loading processes
- 3.8 Peclet number soot penetration correlation
- 3.9 Particle size effect on filtration efficiency
- 3.10 Summary
- 3.11 References

4 Aftertreatment volume downsizing in pre- and post-turbo configuration

- 4.1 Introduction
- 4.2 Modelling methodology
- 4.3 Diesel Oxidation Catalyst
- 4.4 Diesel Particulate Filter
- 4.5 Cost analysis
- 4.6 Aftertreatment volume downsizing effect on engine transient operation
- 4.7 Summary
- 4.8 References

5 Soot deposition analysis

- 5.1 Introduction
- 5.2 Methodology and experimental facilities
- 5.3 Pre-DPF water injection analysis
- 5.4 Peclet number effect on soot deposition
- 5.5 Summary
- 5.6 References

6 Conclusions and future works

- 6.1 Introduction
- 6.2 Main contributions
- 6.3 Future works
- 6.4 References

Bibliography