

# Contents

<b>Acknowledgements</b>	<b>iii</b>
<b>Abstract</b>	<b>xvii</b>
<b>Resumen</b>	<b>xix</b>
<b>Resum</b>	<b>xxiii</b>
<b>1 Introduction</b>	<b>1</b>
1.1 Motivation . . . . .	1
1.2 Objectives . . . . .	13
1.3 Dissertation Outline . . . . .	14
<b>2 Technical Background and Related Work</b>	<b>15</b>
2.1 On-chip Interconnection Networks . . . . .	16
2.1.1 Design Factors . . . . .	16
2.2 Interconnection Network Basics . . . . .	17
2.2.1 Network Topology . . . . .	18
2.2.2 The Routing Device . . . . .	25
2.2.3 Data Units . . . . .	27
2.2.4 Switching . . . . .	28
2.2.5 Flow Control . . . . .	33
2.2.6 Arbitration . . . . .	35
2.2.7 Routing . . . . .	36
2.3 Related Work . . . . .	45
2.3.1 Unicast-based Implementations . . . . .	49

2.3.2	Collective Communication Implementations . . . . .	51
<b>3</b>	<b>The Foundations</b>	<b>55</b>
3.1	Methodology . . . . .	56
3.2	Configuration bits . . . . .	58
3.2.1	Multiple Regions . . . . .	62
3.2.2	Bits Computation . . . . .	63
3.3	Conclusions . . . . .	65
<b>4</b>	<b>Unicast Communication</b>	<b>67</b>
4.1	LBDR: Logic-based Distributed Routing . . . . .	68
4.1.1	Detailed Example . . . . .	72
4.1.2	Arbitration Issues . . . . .	73
4.1.3	More Cores inside a Node . . . . .	76
4.1.4	Configuration Bits Computation . . . . .	78
4.1.5	LBDR <sub>e</sub> . . . . .	80
4.2	Deroutes . . . . .	84
4.2.1	Deroute Bits Computation . . . . .	85
4.3	Forks . . . . .	87
4.3.1	Fork Bits Computation . . . . .	89
4.3.2	Router Implications . . . . .	90
4.4	uLBDR . . . . .	93
4.4.1	Configuration Bits Computation . . . . .	95
4.5	Demonstration . . . . .	96
4.6	Real Implementations . . . . .	100
4.6.1	MPSoC Router Design . . . . .	101
4.6.2	CMP Router Design . . . . .	103
4.7	Evaluation . . . . .	104
4.7.1	Coverage Analysis . . . . .	104
4.7.2	MPSoC Router Overhead . . . . .	107
4.7.3	CMP Router Overhead . . . . .	111
4.7.4	Area and Latency Overhead versus Memory-macro Im- plementations . . . . .	114
4.7.5	Performance Analysis . . . . .	116
4.8	Conclusions . . . . .	123

<b>5 Broadcast/Multicast Communication and the eLBDR Architecture</b>	<b>125</b>
5.1 bLBDR: Broadcast Logic-based Distributed Routing . . . . .	126
5.1.1 A Broadcast is Initiated . . . . .	127
5.1.2 A Router Receives a Broadcast Packet . . . . .	128
5.1.3 Detailed Example . . . . .	131
5.2 SBBM: Signal Bit Based Multicast . . . . .	132
5.2.1 Broadcast Tree . . . . .	135
5.2.2 How the Mechanism Works . . . . .	137
5.2.3 Logic Implementation . . . . .	138
5.2.4 Detailed Example . . . . .	139
5.3 Demonstration . . . . .	140
5.4 Evaluation . . . . .	143
5.4.1 Coverage Analysis . . . . .	143
5.4.2 Area, Latency and Power Breakdown . . . . .	144
5.4.3 Performance Analysis . . . . .	146
5.5 Gathering Unicast and Broadcast Implementations . . . . .	149
5.5.1 <i>eLBDR</i> Architecture . . . . .	150
5.5.2 Evaluation . . . . .	151
5.6 Conclusions . . . . .	154
<b>6 Conclusions</b>	<b>157</b>
6.1 Conclusions . . . . .	157
6.2 Contributions . . . . .	159
6.3 Future Work . . . . .	161
6.4 Publications related to this work . . . . .	162
<b>Bibliography</b>	<b>165</b>