



ELEMENTO REUTILIZADO	COMPLEMENTO	SISTEMA RESULTANTE
<div><div>x64</div><div>x50</div><div>x58</div><div>x280</div><div>x52</div></div> <div>marco carpintería metálica</div>	<div><div>0,5 mm - .020" A - C=1,0 mm 645 - 20%</div><div>0,5 mm - .020" A - C=1,25 mm 470 - 14%</div><div>0,9 mm - .035" A - C=1,8 mm 230 - 23%</div><div>1,0 mm - .040" A - C=1,6 mm 252 - 31%</div><div>1,3 mm - .051" A - C=2,4 mm 129 - 26%</div><div>1,4 mm - .055" A - C=2,4mm 129 - 31%</div><div>1,8 mm - .071" A - C=3,0 mm 82 - 32%</div><div>2,0 mm - 5/64" A - C=3,0 mm 82 - 40%</div><div>2,8 mm - 7/64" A - C=4,0 mm 47 - 44%</div><div>3,17 mm - 1/8" A - C=5,0 mm 30 - 36%</div><div>4,0 mm - 5/32" A - C=6,0 mm 20 - 40%</div><div>4,0 mm - 5/32" A - C=7,0 mm 15 - 29%</div></div> <div>chapa perforada</div>	<div></div> <div>PIEL DE FACHADA_FILTRO VISUAL Y SOLAR</div>
<div><div>x650</div></div> <div>puertas interiores</div>	<div></div> <div>guía metálica + tratamiento para exterior</div>	<div></div> <div>PROTECCIÓN SOLAR</div>
<div><div>20000 m2</div></div> <div>ladrillo triturado</div>	<div><div>64</div><div>49</div><div>31</div><div>LATERAL</div></div> <div>banco-jardinería</div>	<div></div> <div>PARTERRES</div>
<div><div>10000 m2</div></div> <div>escombros hormigón</div>	<div></div> <div>gabiones metálicos</div>	<div></div> <div>FACHADA ED. INSTALACIONES</div>