

CONTENTS

1.	<u>INTRODUCTION</u>	26
1.1.	Background	26
1.2.	Scientific and technical contributions	29
1.3.	Structure of the thesis	30
2.	<u>OBJECTIVES</u>	33
3.	<u>BIBLIOGRAPHIC REVIEW</u>	34
3.1.	Electroplating process	34
3.2.	Brass plating process	35
3.3.	Replacement of cyanide in the brass plating bath	36
3.4.	The use of EDTA as a complexing agent	37
3.5.	Electroplating industry waste	40
3.6.	Conventional treatment of wastewaters from electroplating industries	40
3.7.	Electrodialysis	41
3.8.	Chronopotentiometry	47
3.8.1.	Transition time	51
3.8.2.	Fraction of conductive area	53
3.8.3.	Transport number	55
3.8.4.	Fouling and scaling	55
3.9.	Current-voltage curves	58
3.9.1.	Concentration polarization and limiting current density	60
3.9.2.	The presence of additional inflection points in chronopotentiograms and current-voltage curves	66
3.9.3.	Electric resistance	68

3.9.4.	Plateau length	71
3.10.	Electrodialysis operation under overlimiting conditions	74
3.10.1.	Electroconvection	75
3.10.2.	Gravitational convection	79
3.10.3.	Water splitting	80
4.	<u>MATERIALS AND METHODS</u>	83
4.1.	Ion-exchange membranes	83
4.2.	Electrochemical cell for chronopotentiometric measurements	84
4.2.1.	Obtaining of current-voltage curves by chronopotentiometry	85
4.3.	Topic I: Chronopotentiometric study for evaluating the effect of the membrane morphology on the transport properties of Cu(II) through a homogeneous and a heterogeneous ion-exchange membrane	85
4.3.1.	Working solutions	85
4.3.2.	Visualization of the membranes structure	86
4.3.3.	Determination of the transport and membrane properties	86
4.4.	Topic II: Chronopotentiometric study for evaluating the transport properties of the anion-exchange membrane used in the treatment of the synthetic cyanide-free wastewater from brass electrodeposition	87
4.4.1.	Working solutions	87
4.5.	Topic III: Treatment of the synthetic cyanide-free wastewater, by electrodialysis in underlimiting and overlimiting condition, from the brass electrodeposition with EDTA	89
4.5.1.	Electrodialysis bench system	89
4.5.2.	Experimental procedure	91
4.5.3.	Determination of the limiting current density of the membranes in the ED stack	92

4.5.4.	Working solutions	92
4.5.5.	Chronopotentiometric measurements	93
4.5.6.	Analytical methods	93
4.5.7.	Cleaning procedure of the membranes	94
4.6.	Topic IV: Evaluation of brass electrodeposition at RDE from cyanide-free bath and the recovery of the metals and EDTA extracted, by electrodialysis, into the bath	95
4.6.1.	Cyclic voltammetry	96
4.6.2.	Electrodeposition tests	97
5.	<u>RESULTS AND DISCUSSION</u>	99
5.1.	Topic I: Chronopotentiometric study for evaluating the effect of the membrane morphology on the transport properties of Cu(II) through a homogeneous and a heterogeneous ion-exchange membrane	99
5.1.1.	Visualization of the membranes structure	99
5.1.2.	Determination of fraction of conductive area of the membranes	99
5.1.3.	Evaluation of chronopotentiometric curves of solutions with copper	101
5.1.4.	Evaluation of the CVC behavior for both membranes	104
5.1.5.	Effect of Cu ²⁺ concentration on the transport properties across the membranes	106
5.1.6.	Evaluation of chronopotentiograms of both membranes with a more concentrated solution	110
5.1.7.	Conclusions	113
5.2.	Topic II: Chronopotentiometric study for evaluating the transport properties of the anion-exchange membrane used in the treatment of the synthetic cyanide-free wastewater from brass electrodeposition	114
5.2.1.	Effect of pH	116
5.2.2.	Effect of the Cu ²⁺ /Zn ²⁺ molar ratio	123

5.2.3.	Effect of EDTA	128
5.2.4.	Conclusions	132
5.3.	Topic III: Treatment of the synthetic cyanide-free wastewater, by electrodialysis in underlimiting and overlimiting condition, from the brass electrodeposition with EDTA	133
5.3.1.	Obtaining of current-voltage curves in the electrodialysis stack	134
5.3.2.	Electrodialysis	135
5.3.2.1.	Evaluation of the solution conductivity	137
5.3.2.2.	Percent concentration and percent extraction	139
5.3.2.3.	Mass balance	146
5.3.3.	Chronopotentiometric measurements after the ED tests	147
5.3.4.	Cleaning of the membranes	153
5.3.4.1.	Evaluation of current-voltage curves	153
5.3.4.2.	Evaluation of chronopotentiometric curves	155
5.3.4.2.1.	Chronopotentiograms of the anion-exchange membrane	156
5.3.4.2.2.	Chronopotentiograms of the cation-exchange membrane	158
5.3.4.3.	FTIR-ATR analysis	159
5.3.4.3.1.	Anion-exchange membrane	159
5.3.4.3.2.	Cation-exchange membrane	161
5.3.4.4.	SEM/EDS analysis	163
5.3.5.	Conclusions	165
5.4.	Topic IV: Evaluation of brass electrodeposition at RDE from cyanide-free bath and the recovery of the metals and EDTA extracted, by electrodialysis, into the bath	167
5.4.1.	Voltammetric study	167
5.4.1.1.	Influence of the rotation speed	167

5.4.1.2.	Influence of ions concentration	171
5.4.2.	Electrodeposition tests	173
5.4.2.1.	Potentiostatic mode	173
5.4.2.2.	Galvanostatic mode	177
5.4.2.2.1.	Influence of the charge density	180
5.4.2.3.	Addition of the concentrated solution obtained from the wastewater treatment into the bath	182
5.4.2.4.	Concentration adjustment of the solution from electrodialysis	185
5.4.3.	Conclusions	186
6.	<u>FINAL CONCLUSIONS</u>	188
6.1.	Final conclusions of topic I	188
6.2.	Final conclusions of topic II	189
6.3.	Final conclusions of topic III	189
6.4.	Final conclusions of topic IV	190
	REFERENCES	191
	Appendix	218