


Elemento	Pos.	Diám.	No.	Esquema (cm)	Long. (cm)	Total (cm)	S-400 (kg)
P8-P89	1	ø16	4	141	155	620	9.8
	2	ø6	7	24	105	735	1.6
					Total=105	185	56.0

Acero: S-400 (502 kg). Cantidad: 384.93 kg/m³
Hormigón: C25/30 (0.13 m³) Tamaño máximo del árido: 15 mm
Encofrado: 1.74 m² Recubrimiento geométrico: 3.0 cm

Pos.	Diám.	No.	Long. (cm)	Total (cm)	x 4 (cm)
1	ø16	4	155	620	2480
2	ø6	7	105	735	2940

4E1020/730 Arranca en la cota +0.000
730



P8-P89	1	ø16	4	141	155	620	9.8
	2	ø6	7	24	105	735	1.6
					Total=105	185	56.0

Acero: S-400 (251 kg). Cantidad: 192.47 kg/m³
Hormigón: C25/30 (0.13 m³) Tamaño máximo del árido: 15 mm
Encofrado: 1.74 m² Recubrimiento geométrico: 3.0 cm

Pos.	Diám.	No.	Long. (cm)	Total (cm)	x 2 (cm)
1	ø16	4	155	620	1240
2	ø6	7	105	735	1470

4E1020/730 Arranca en la cota +0.000
730