





Elemento	Pos.	Diám.	No.	Esquema (cm)	Long. (cm)	Total (cm)	S-400 (kg)
PB7-PB5-P100-P103	1	Ø12	12	647	647	7764	68.9
	2	Ø6	43	105	105	4515	10.0
	3	Ø6	172	36	36	6192	13.7
	4	Ø12	12	135	135	1620	14.4
	5	Ø6	3	95	95	285	0.6
	6	Ø6	12	33	33	396	0.9
Total+100					119.4	119.4	119.4

Pos.	Diám.	No.	Long. (cm)	Total (cm)	x 4 (cm)
1	Ø12	12	647	7764	31056
2	Ø6	43	105	4515	18060
3	Ø6	172	36	6192	24768
4	Ø12	12	135	1620	6480
5	Ø6	3	95	285	1140
6	Ø6	12	33	396	1584

Acero: S-400 (487.8 kg). Cuentía: 697.17 kg/m3	
Hormigón: C25/30 (0.59 m3) Tamaño máximo del árido: 15 mm	Planta: cubierta exterior
Encofrado: 7.80 m2	Recubrimiento geométrico: 3.0 cm



P95-P92-P102-P96	1	Ø20	4	645	80	730	2920	72.0
	2	Ø16	4	705		705	2820	44.5
	3	Ø6	33	24		105	3465	7.7
	4	Ø20	4	165		195	780	19.2
	5	Ø16	4	145		175	700	11.0
	6	Ø6	3	21		93	279	0.6
Total+100								119.5
								119.5
								119.5
								119.5
								119.5
								119.5

Pos.	Diám.	No.	Long. (cm)	Total (cm)	x 4 (cm)
1	Ø20	4	730	2920	11680
2	Ø16	4	705	2820	11280
3	Ø6	33	105	3465	13860
4	Ø20	4	195	780	3120
5	Ø16	4	175	700	2800
6	Ø6	3	93	279	1116

Acero: S-400 (546.5 kg). Cuentía: 934.23 kg/m3	
Hormigón: C25/30 (0.59 m3) Tamaño máximo del árido: 15 mm	Planta: cubierta exterior
Encofrado: 7.80 m2	Recubrimiento geométrico: 3.0 cm

